

EXPO SYSTEM LED FI 85 3100LM 36ST I KL IP20 CZARNY 840 (28W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	254406
Ingress protection:	IP20
Nominal power [W]:	28
Luminous flux [lm]*:	3100
Colour temperature [K]:	4000
Electrical protection class:	I
Energy efficiency class:	E
Colour of the body:	black
Diffuser type:	lens
Beam angle [°]:	36

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors. Optional specialized filters to highlight meat stands, bread or vegetables. Version CRI (Ra) > 90 available on request.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector


EXPO SYSTEM LED FI 85 3100LM 36ST I KL IP20 CZARNY 840 (28W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	28	Dimensions (H/W/T/S) [mm]:	Ø85/255mm
Light source:	LED module	Ingress protection:	IP20
Colour temperature [K]:	4000	Mounting version:	track, surface
Luminous flux [lm]:	3100	Working temperature [°C]:	from -20 to +35
Rated power of the luminaire [W]:	29	Tilt angle adjustment [°]:	355
Diffuser type:	lens	Net weight [kg]:	1.100
Supply voltage [V]:	220-240	CE certificate:	45/2020
Beam angle [°]:	36	Index:	254406
Frequency [Hz]:	50 - 60	EAN:	5905963254406
Colour rendering index:	>80	Category type:	spotlight
Colour of the body:	black	ETIM class:	EC001744
Luminous efficacy [lm/W]:	106	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Energy efficiency class:	E	Warranty [years]:	2
Electrical protection class:	I	Manual:	Download PDF
Diffuser material:	PMMA	Plik LDT:	Download
Material of the body:	aluminium		

LIGHT CURVES



EXPO SYSTEM LED FI 85 3100LM 36ST I KL IP20 CZARNY 840 (28W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



EXPO SYSTEM LED honeycomb (255120)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 45/2020