EXPO LED 2 Ø107 1319LM 45° BLACK 830 (10W)

DETAILED CARD





TECHNICAL PARAMETERS

Ingress protection: IP20

Rated power of the luminaire [W]*: 10

Luminous flux [lm]*: 1319

Colour temperature [K]: 3000

Colour rendering index: >80

Energy efficiency class: D

Material of the body: aluminium

Diffuser material: PC

Diffuser type: transparent

Optics material: PC

CHARACTERISTICS

High quality aluminum projector with LED light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.



EXPO LED 2 Ø107 1319LM 45° BLACK 830 (10W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	969607
EAN:	5905963969607
Light source:	LED
Rated power of the luminaire [W]:	10
Luminous flux [lm]:	1319
Luminous efficacy [lm/W]:	132
Energy efficiency class:	D
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	>80
Beam angle [°]:	45
Diffuser material:	PC
Diffuser type:	transparent

Optics material:	PC
Optics:	reflector
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	Ø107/225
Ingress protection:	IP20
Net weight [kg]:	1.100
Warranty [years]:	5
LED lifespan L70B50 [h]:	73000
LED lifespan L80B20 [h]:	63000
LED lifespan L90B10 [h]:	59000
Warranty [years]:	5
Manual:	Download PDF

Card creation date: 12 July 2023



