DETAILED CARD



TECHNICAL PARAMETERS

Index:	254673
Ingress protection:	IP20
Nominal power [W]:	18
Luminous flux [lm]*:	1900
Colour temperature [K]:	4000
Electrical protection class:	1
Energy efficiency class:	E
Colour of the body:	black
Diffuser type:	lens
Beam angle [°]:	36

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability. Immediate ignition without flicker makes it the best replacement for metal halide or halogen sources projectors. Optional specialized filters to highlight meat stands, bread or vegetables. Version CRi (Ra)> 90 available on request.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector




TECHNICAL PARAMETERS TABLE

Light source:	LED module	
Nominal power [W]:	18	
Rated power of the luminaire [W]:	19.80	
Supply voltage [V]:	220-240	
Frequency [Hz]:	50 - 60	
Luminous flux [Im]:	1900	
Luminous efficacy [lm/W]:	95	
Energy efficiency class:	E	
Electrical protection class:	1	
Colour temperature [K]:	4000	
Colour rendering index:	90	
Beam angle [°]:	36	
Diffuser material:	PMMA	
Diffuser type:	lens	
Material of the body:	aluminium	
Colour of the body:	black	

Ø85/255mm
IP20
track, surface
from -20 to +35
355
1.100
<u>45/2020</u>
254673
5905963254673
spotlight
EC001744
Risk Group 1 (no photobiological hazard under normal behavioral limitation)
2
Download PDF
Download

LIGHT CURVES




DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
255106	EXPO SYSTEM LED surface mounting base black
255113	EXPO SYSTEM LED surface mounting base white
255120	EXPO SYSTEM LED honeycomb



EXPO SYSTEM LED surface mounting base black (255106)



EXPO SYSTEM LED surface mounting base white (255113)



EXPO SYSTEM LED honeycomb (255120)

Card creation date: 10 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

