SHOP SYSTEM T LED EVO Ø106 2820LM 30° BLACK 930 (33W)

DETAILED CARD





TECHNICAL PARAMETERS

Index:	968525
Light source:	LED
Rated power of the luminaire [W]*:	33
Nominal power [W]:	28
Luminous flux [lm]*:	2820
Colour temperature [K]:	3000
Energy efficiency class:	F
Colour rendering index:	>90
Ingress protection:	IP20
Diffuser material:	glass

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.



SHOP SYSTEM T LED EVO Ø106 2820LM 30° BLACK 930 (33W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	968525
EAN:	5905963968525
Light source:	LED
Nominal power [W]:	28
Rated power of the luminaire [W]:	33
Luminous flux [lm]:	2820
Luminous efficacy [lm/W]:	86
Energy efficiency class:	F
Electrical protection class:	1
Colour temperature [K]:	3000
Colour rendering index:	>90
Power factor:	0.98
Beam angle [°]:	30°
Diffuser material:	glass
Diffuser type:	transparent

Optics material:	aluminium
Optics:	reflector
Material of the body:	aluminium
Colour of the body:	black
Dimensions (H/W/T/S) [mm]:	Ø106/112/140
Ingress protection:	IP20
Net weight [kg]:	1.310
Warranty [years]:	5
Category type:	spotlight
LED lifespan L70B50 [h]:	60000
LED lifespan L80B20 [h]:	49000
LED lifespan L90B10 [h]:	46000
Warranty [years]:	5
Manual:	Download PDF
CE certificate:	294/2023

Card creation date: 15 December 2020



