SHOP SYSTEM T LED EVO Ø106 3500LM 45° BLACK 840 (33W)

DETAILED CARD





TECHNICAL PARAMETERS

| Index: | 968679 |
|------------------------------------|--------|
| Light source: | LED |
| Rated power of the luminaire [W]*: | 33 |
| Nominal power [W]: | 28 |
| Luminous flux [lm]*: | 3500 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | Е |
| Colour rendering index: | >80 |
| Ingress protection: | IP20 |
| Diffuser material: | glass |
| | |

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.



SHOP SYSTEM T LED EVO Ø106 3500LM 45° BLACK 840 (33W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| Index: | 968679 |
|-----------------------------------|---------------|
| EAN: | 5905963968679 |
| Light source: | LED |
| Nominal power [W]: | 28 |
| Rated power of the luminaire [W]: | 33 |
| Luminous flux [lm]: | 3500 |
| Luminous efficacy [lm/W]: | 107 |
| Energy efficiency class: | Е |
| Electrical protection class: | I |
| Colour temperature [K]: | 4000 |
| Colour rendering index: | >80 |
| Power factor: | 0.98 |
| Beam angle [°]: | 45° |
| Diffuser material: | glass |
| Diffuser type: | transparent |

| Optics material: | aluminium |
|----------------------------|--------------|
| Optics: | reflector |
| Material of the body: | aluminium |
| Colour of the body: | black |
| Dimensions (H/W/T/S) [mm]: | Ø106/112/140 |
| Ingress protection: | IP20 |
| Net weight [kg]: | 1.310 |
| Warranty [years]: | 5 |
| Category type: | spotlight |
| LED lifespan L70B50 [h]: | 60000 |
| LED lifespan L80B20 [h]: | 49000 |
| LED lifespan L90B10 [h]: | 46000 |
| Warranty [years]: | 5 |
| Manual: | Download PDF |
| CE certificate: | 294/2023 |

Card creation date: 15 December 2020



