

SHOP SYSTEM T LED EVO Ø106 3840LM 15° WHITE 830 (39W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	968020
Light source:	LED
Rated power of the luminaire [W]*:	39
Nominal power [W]:	34
Luminous flux [lm]*:	3840
Colour temperature [K]:	3000
Energy efficiency class:	E
Colour rendering index:	>80
Ingress protection:	IP20
Diffuser material:	glass

CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

SHOP SYSTEM T LED EVO Ø106 3840LM 15° WHITE 830 (39W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	968020	Optics material:	aluminium
EAN:	5905963968020	Optics:	reflector
Light source:	LED	Material of the body:	aluminium
Nominal power [W]:	34	Colour of the body:	white
Rated power of the luminaire [W]:	39	Dimensions (H/W/T/S) [mm]:	Ø106/112/140
Luminous flux [lm]:	3840	Ingress protection:	IP20
Luminous efficacy [lm/W]:	99	Net weight [kg]:	1.310
Energy efficiency class:	E	Warranty [years]:	5
Electrical protection class:	I	Category type:	spotlight
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	60000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	49000
Power factor:	0.98	LED lifespan L90B10 [h]:	46000
Beam angle [°]:	15°	Warranty [years]:	5
Diffuser material:	glass	Manual:	Download PDF
Diffuser type:	transparent	CE certificate:	294/2023

Card creation date: 15 December 2020
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 294/2023