

# SHOP SYSTEM T LED EVO Ø106 3840LM 45° BLACK 830 (39W)

DETAILED CARD



## TECHNICAL PARAMETERS

Index:	968624
Light source:	LED
Rated power of the luminaire [W]*:	39
Nominal power [W]:	34
Luminous flux [lm]*:	3840
Colour temperature [K]:	3000
Energy efficiency class:	E
Colour rendering index:	>80
Ingress protection:	IP20
Diffuser material:	glass

## CHARACTERISTICS

High quality aluminum projector with LED COB light source. Universal application with track system. Lack of ultraviolet emission or infrared radiation, high color rendering index, high luminous efficacy and durability.

## APPLICATION

Possible use of specialized filters to highlight food stands. As accentuating lighting in commercial buildings, museums, exhibition halls and offices. For connection with track systems in the color of the projector.

# SHOP SYSTEM T LED EVO Ø106 3840LM 45° BLACK 830 (39W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	968624	Optics material:	aluminium
EAN:	5905963968624	Optics:	reflector
Light source:	LED	Material of the body:	aluminium
Nominal power [W]:	34	Colour of the body:	black
Rated power of the luminaire [W]:	39	Dimensions (H/W/T/S) [mm]:	Ø106/112/140
Luminous flux [lm]:	3840	Ingress protection:	IP20
Luminous efficacy [lm/W]:	99	Net weight [kg]:	1.310
Energy efficiency class:	E	Warranty [years]:	5
Electrical protection class:	I	Category type:	spotlight
Colour temperature [K]:	3000	LED lifespan L70B50 [h]:	60000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	49000
Power factor:	0.98	LED lifespan L90B10 [h]:	46000
Beam angle [°]:	45°	Warranty [years]:	5
Diffuser material:	glass	Manual:	<a href="#">Download PDF</a>
Diffuser type:	transparent	CE certificate:	<a href="#">294/2023</a>