

TYTAN 2 LED BASIC MULTI 1150MM 4400-7150LM 840 IP66

DETAILED CARD



TECHNICAL PARAMETERS

Index:	940880
Ingress protection:	IP66
Impact resistance:	IK09
Rated power [W] - range:	29/37/44/51
Luminous flux of the luminaire [lm] - range:	4400/5400/6300/7150
Colour temperature [K]:	4000
Material of the body:	PC
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

TYTAN 2 LED BASIC MULTI is a basic line of lighting fixtures that provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC MULTI includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy up to 158 lm/W. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of +/-50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation. The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of four settings (rated power of the luminaire [W]/luminous flux of the fitting [lm]): 18W-31W - 1. 18W/2700 lm; 2. 22W/3250 lm; 3. 26W/3800 lm; 4. 32W/4300 lm; 22W-38W - 1. 22W/3300 lm; 2. 27W/4000 lm; 3. 31W/4500 lm; 4. 38W/5300 lm; 26W-46W - 1. 26W/4050 lm; 2. 32W/4950 lm; 3. 39W/5800 lm; 4. 46W/6600 lm; 29W-51W - 1. 29W/4400 lm; 2. 37W/5400 lm; 3. 44W/6300 lm; 4. 51W/7150 lm; 32W-55W - 1. 32W/5050 lm; 2. 40W/6200 lm; 3. 47W/7250 lm; 4. 55W/8250 lm; 34W-59W - 1. 34W/5150 lm; 2. 42W/6200 lm; 3. 51W/7250 lm; 4. 59W/8150 lm;

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.

TYTAN 2 LED BASIC MULTI 1150MM 4400-7150LM 840 IP66

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	940880	Dimensions (H/W/T/S) [mm]:	1152/85/80
EAN:	5905963940880	Impact resistance:	IK09
Light source:	LED module	Ingress protection:	IP66
Rated power [W] - range:	29/37/44/51	Mounting version:	surface, suspended
Luminous flux of the luminaire [lm] - range:	4400/5400/6300/7150	Working temperature [°C]:	from -20 to +40
Supply voltage [V]:	220 - 240	Net weight [kg]:	1.600
Frequency [Hz]:	50 - 60	LED lifespan L70B50 [h]:	90000
Luminous efficacy [lm/W]:	152	LED lifespan L80B20 [h]:	57000
Energy efficiency class:	C	LED lifespan L90B10 [h]:	28000
Electrical protection class:	I	Additional accessories:	protective grid, adjustable handle
Colour temperature [K]:	4000	The number of implement units:	1
Colour rendering index:	80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	≤ 3	Warranty [years]:	5
Power factor:	0.90	CE certificate:	451/2023
Exchangeable source:	yes	ENEC Certificate:	0310/ENEC/23
Diffuser material:	PC	PZH certificate:	B-BK-60212-0152/20
Diffuser type:	matt	HACCP:	852/2004
Material of the body:	PC	Manual:	Download PDF
Colour of the body:	grey	Plik LDT:	Download

LIGHT CURVES



TYTAN 2 LED BASIC MULTI 1150MM 4400-7150LM 840 IP66

DETAILED CARD

TECHNICAL DETAILS



regulowane uchwyty / adjustable
handles / einstellbare Halterungen



system zwieszania klosza / suspension
system of the diffuser / hängende
Diffusor




wybór miejsca zasilania / choosing a
place of power supply /
Stromversorgungsanschluss von
mehreren Seite möglich

TYTAN 2 LED BASIC MULTI 1150MM 4400-7150LM 840 IP66

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
60000006	M16 stuffing box plug various PA black M-16 - BPM-21
80000378	Cable gland PG 13.5 Titanium PA 6.6 gray with nut



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (60000006)