DETAILED CARD





TECHNICAL PARAMETERS

Index: 940958

Ingress protection: IP66

Impact resistance: IK09

Rated power [W] - range: 34/42/51/59

Luminous flux of the luminaire [lm] -

range:

5150/6200/7250/8150

Colour temperature [K]: 4000

Material of the body: PC

Colour of the body: grey

Diffuser material: PC

CHARACTERISTICS

TYTAN 2 LED BASIC MULTI is a basic line of lighting fixtures that provides an excellent alternative to traditional fluorescent lamps. The lighting fixture has been designed from scratch. TYTAN 2 LED BASIC MULTI includes new solutions which improve the light distribution and the temperature balance. The new LED panels ensure high luminous efficacy up to 158 lm/W. This provides the required level of lighting along with significant energy savings. The lighting fixture includes many improvements which facilitate and speed up the installation process: a solution involving the integration of the diffuser with the LED panel, a diffuser suspension system, and adjustable mounting brackets with an installation tolerance of +/-50 mm. As a standard, the fixture is equipped with robust clips made of stainless steel (INOX). The body of the fixture and the diffuser are resistant to UV radiation. The MULTI luminaire version allows individual configuration: thanks to the built-in microswitch, it is possible to choose one of four settings (rated power of the luminaire [W]/luminous flux of the fitting [Im])

APPLICATION

The multifunctional LED lamp is designed for use in areas with high requirements for dust and water resistance. Especially recommended for lighting public facilities, including hospitals, educational facilities, halls, garages, passages, warehouses, shops, food industry, commercial and industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals, and underground passages. The luminaire is ideal for new lighting applications as well as replacing traditional fluorescent luminaires with energy-saving LED solutions. Its design is adapted for surface and suspended mounting.




DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	940958
EAN:	5905963940958
Light source:	LED module
Rated power [W] - range:	34/42/51/59
Luminous flux of the luminaire [lm] - range:	5150/6200/7250/8150
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	151
Energy efficiency class:	С
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.90
Exchangeable source:	yes
Diffuser material:	PC
Diffuser type:	matt
Material of the body:	PC
Colour of the body:	grey

Dimensions (H/W/T/S) [mm]:	1152/85/80
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	surface, suspended
Working temperature [°C]:	from 0 to +35
Emergency lighting [h]:	3
Net weight [kg]:	1.800
LED lifespan L70B50 [h]:	90000
LED lifespan L80B20 [h]:	57000
LED lifespan L90B10 [h]:	28000
Additional accessories:	protective grid, adjustable handle
The number of implement units:	1
Photobiological safety:	Risk Group 1 (no photobiological
Photobiological safety.	hazard under normal behavioral limitation)
Warranty [years]:	
,	limitation)
Warranty [years]:	limitation) 2 / 0.5 (battery)
Warranty [years]: CE certificate:	limitation) 2 / 0.5 (battery) 451/2023
Warranty [years]: CE certificate: ENEC Certificate:	limitation) 2 / 0.5 (battery) 451/2023 0310/ENEC/23

LIGHT CURVES



DETAILED CARD

TECHNICAL DETAILS



regulowane uchwyty / adjustable handles / einstellbare Halterungen



system zwieszania klosza / suspension system of the diffuser / hängende Diffusor



wybór miejsca zasilania / choosing a place of power supply / Stromversorgungsanschluss von mehreren Seite möglich



DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
907913	TYTAN LED. ATLAS LED - protective grid 1152mm
907920	TYTAN LED. ATLAS LED - protective grid 1432mm
16000507	Breathable gland gray M20*1.5 IP68
6000006	M16 stuffing box plug various PA black M-16 - BPM-21
80000378	Cable gland PG 13.5 Titanium PA 6.6 gray with nut



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



TYTAN LED. ATLAS LED - protective grid 1152mm (907913)



TYTAN LED. ATLAS LED - protective grid 1432mm (907920)



Breathable gland gray M20*1.5 IP68 (16000507)



M16 stuffing box plug various PA black M-16 - BPM-21 (6000006)

Card creation date: 14 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

