

# SITE LITE FUTURE LED 2300LM 840 IP54 GREY (20W) ACCU

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	621444
<b>Nominal power [W]:</b>	20
<b>Colour temperature [K]:</b>	4000
<b>Luminous flux [lm]*:</b>	2000
<b>Ingress protection:</b>	IP54/20
<b>Electrical protection class:</b>	III

## CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging. Thanks to the built-in Li-ion battery (2,000 mAh), the lamp can operate independently of the mains.

Battery operation modes:

- Mode 1: 650lm / 6h working time
- Mode 2: 1000lm / 4h working time
- Mode 3: 2200lm / 2h working time

Accessories available:

- magnets screwed to the lamp base
- tripod holder

## APPLICATION

The luminaire will provide precise illumination of the workplace.

# SITE LITE FUTURE LED 2300LM 840 IP54 GREY (20W) ACCU

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Nominal power [W]:	20	LED lifespan L70B50 [h]:	50000
Index:	621444	Beam angle [°]:	120
Colour temperature [K]:	4000	Light distribution type:	symmetric
EAN:	590596621444	Battery:	Li-Ion 18,5V
Luminous flux [lm]:	2000	Battery capacity [mAh]:	2000
Category type:	general construction site lighting	Diffuser material:	PC
Light source:	LED module	Diffuser type:	OPAL
Rated power of the luminaire [W]:	21	Material of the body:	PP+T
Supply voltage [V]:	220 – 240	Colour of the body:	grey
Frequency [Hz]:	50 – 60	Dimensions (H/W/T/S) [mm]:	198/154
Luminous efficacy [lm/W]:	115	Ingress protection:	IP54/20
Energy efficiency class:	E	Working temperature [°C]:	from 0 to +25
Electrical protection class:	III	Wire type:	PCV
Colour rendering index:	>80	Cable length [m]:	2
SDCM:	≤ 3	Switch:	yes
Power factor:	0.75	Net weight [kg]:	1.400
Charging time [h:min]:	4	Warranty [years]:	2
Battery life [h:min]:	6	Manual:	<a href="#">Download PDF</a>

Card creation date: 04 February 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 265/2023