SITE LITE FUTURE LED 2300LM 840 IP54 GREY (20W) ACCU

DETAILED CARD



TECHNICAL PARAMETERS

Index:	621444
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2000
Ingress protection:	IP54/20
Electrical protection class:	III

CHARACTERISTICS

Modern and efficient construction site luminaire shining in all directions (360°). Provides even and stable light distribution all over the room. The body is made of highly impact-resistant plastic. Anti-glare diffuser has been made of frosted polycarbonate (PC). The luminaire is equipped with a protruding, folding hook for hanging.Thanks to the built-in Li-ion battery (2,000 mAh), the lamp can operate independently of the mains.

Battery operation modes:

- Mode 1: 650lm / 6h working time
- Mode 2: 1000lm / 4h working time
- Mode 3: 2200lm / 2h working time

Accessories available:

- magnets screwed to the lamp base
- tripod holder

APPLICATION

The luminaire will provide precise illumination of the workplace.

SITE LITE FUTURE LED 2300LM 840 IP54 GREY (20W) ACCU

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	621444	**LED lifespan L70B50 [h]:**	50000
EAN:	590596621444	**Beam angle [°]:**	120
Category type:	general construction site lighting	**Light distribution type:**	symmetric
Light source:	LED module	**Battery:**	Li-Ion 18,5V
Nominal power [W]:	20	**Battery capacity [mAh]:**	2000
Rated power of the luminaire [W]:	21	**Diffuser material:**	PC
Luminous flux [lm]:	2000	**Diffuser type:**	OPAL
Supply voltage [V]:	220 – 240	**Material of the body:**	PP+T
Frequency [Hz]:	50 – 60	**Colour of the body:**	grey
Luminous efficacy [lm/W]:	115	**Dimensions (H/W/T/S) [mm]:**	198/154
Energy efficiency class:	E	**Ingress protection:**	IP54/20
Electrical protection class:	III	**Working temperature [°C]:**	from 0 to +25
Colour temperature [K]:	4000	**Wire type:**	PCV
Color rendering index (Ra) >:	80	**Cable length [m]:**	2
SDCM:	3	**Switch:**	yes
Power factor:	0.75	**Net weight [kg]:**	1.400
Charging time [h:min]:	4	**Warranty [years]:**	2
Battery life [h:min]:	6	**Manual:**	Download PDF

Card creation date: 04 February 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 265/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl