GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

Index:	901263
Light source:	LED module
Rated power of the luminaire [W]*:	227
Luminous flux [lm]*:	33144
Colour temperature [K]:	4000
Diffuser material:	PC
Diffuser type:	matt
Diffuser colour:	white
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	740/420/320

CHARACTERISTICS

Lightweight and very powerful portable LED floodlight for professional use. Provides even and stable directional illumination. The lamp is made of impact-resistant polypropylene (PP). The anti-glare diffuser made of polycarbonate (PC), despite its matte surface, transmits up to 80% of the light emitted by the LED. It has an ergonomic carrying handle. Standard: rubber cable H07RN-F 3×1.5mm2 (5m). With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and the maximum degree of impact resistance are particularly important in the lighting of construction sites or in the work of services intervening at various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. Its light weight makes it easy to use for workplace lighting in industrial halls or finishing work.

APPLICATION

Temporary lighting for construction site, finishing works, outdoor earthworks, road and highway repair, Especially useful for mobile services , emergency services, police, military, firefighters, construction crews, electricians, railroad repair, etc.

GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	901263
EAN:	5905963901263
Light source:	LED module
Rated power of the luminaire [W]:	227
Colour temperature [K]:	4000
Luminous flux [lm]:	33144
Supply voltage [V]:	230
Frequency [Hz]:	50
Luminous efficacy [lm/W]:	137
Energy efficiency class:	C
Electrical protection class:	I
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
Diffuser material:	PC

Diffuser type:	matt
Diffuser colour:	white
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	740/420/320
Impact resistance:	IK10
Ingress protection:	IP54
Plug type:	UNI-SCHUKO
Socket type:	PL-FR
Sockets:	2
Wire type:	H07RN- 3x1,5mm2
Cable length [m]:	5
Net weight [kg]:	7.700
Warranty [years]:	5
CE certificate:	125/2023
Manual:	Download PDF

GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
000300	Adapter plate with click function for mounting the Giant Luminaire on the tripod
000294	Steel tripod 3 m



Steel tripod 3 m (000294)

Card creation date: 23 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 125/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl