### **GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS**

DETAILED CARD



### **TECHNICAL PARAMETERS**

Index:	901263	
Light source:	LED module	
Rated power of the luminaire [W]*:	227	
Luminous flux [lm]*:	33144	
Colour temperature [K]:	4000	
Diffuser material:	PC	
Diffuser type:	MAT	
Diffuser colour:	white	
Colour of the body:	grey	
Dimensions (H/W/T/S) [mm]:	740/420/320	

### **CHARACTERISTICS**

Lightweight and very powerful portable LED floodlight for professional use. Provides even and stable directional illumination. The lamp is made of impactresistant polypropylene (PP). The anti-glare diffuser made of polycarbonate (PC), despite its matte surface, transmits up to 80% of the light emitted by the LED. It has an ergonomic carrying handle. Standard: rubber cable H07RN-F 3×1.5mm2 (5m). With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and the maximum degree of impact resistance are particularly important in the lighting of construction sites or in the work of services intervening at various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. Its light weight makes it easy to use for workplace lighting in industrial halls or finishing work.

#### APPLICATION

Temporary lighting for construction site, finishing works, outdoor earthworks, road and highway repair, Especially useful for mobile services, emergency services, police, military, firefighters, construction crews, electricians, railroad repair, etc.



## GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS

DETAILED CARD

#### **TECHNICAL PARAMETERS TABLE**

Index:901263Power factor:0.99Rated power of the luminaire [W]:27Diffuser material:PCEAN:505963901263Diffuser type:MATLuminous flux [Im]:3144Diffuser colour:whiteLight source:LED moduleColour of the body:greyColour temperature [K]:4000Dimensions (H/W/T/S) [mm]:40/420/320Ingers protection:P54Sockets:2Pug type:VIN-SCHUKOWire type:HORN-3x1,5mm2Supply voltage [V]:S0Cable length [m]:5Frequency [Hz]:S0Warranty [years]:5Ingers protection class:ICalcurention00033Supply roltage [Im]:SaEctertificate:000393Frequency [Im]:SaEctertificate:25/2023Supply roltage [Im]:SaSaSacets:Supply roltage [Im]:SaSacets:Sacets:Supply roltage [Im]:SaSacets:Sacets:Supply roltage [Im]:Sacets:Sacets:Sacets:Supply roltage [Im]:Sacets:Sacets:Sacets				
EAN:5905963901263Diffuser type:MATLuminous flux [lm]:33144Diffuser colour:whiteLight source:LED moduleColour of the body:greyColour temperature [K]:4000Dimensions (H/W/T/S) [mm]:740/420/320Ingress protection:IP54Impact resistance:IK10Socket type:PL-FRSockets:2Plug type:UNI-SCHUKOVire type:HO7RN-3x1,5mm2Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.00Luminous efficacy [im/W]:137Warranty [years]:5Energy efficiency class:ICalcource125/2023Jour endering index:880Manuai:Download PDE	Index:	901263	Power factor:	0.99
Luminous flux [lm]:33144Diffuser colour:whiteLight source:LED moduleColour of the body:greyColour temperature [K]:4000Dimensions (H/W/T/S) [mm]:740/420/320Ingress protection:IP54Impact resistance:K10Socket type:PL-FRSockets:2Plug type:UNI-SCHUKOWire type:H07RN-3x1,5mm2Supply voltage [V]:50Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.00Luminous efficacy [lm/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:00393Bectrical protection class:180Manual:Download PDF	Rated power of the luminaire [W]:	227	Diffuser material:	PC
Light source:LED moduleColour fthe body:greyColour temperature [K]:4000Dimensions (H/W/T/S) [mm]:740/420/320Ingress protection:IP54Impact resistance:IK10Socket type:PL-FRSockets:2Plug type:UNI-SCHUKOWire type:H07RN-3x1,5mm2Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [im/W]:137Warranty [years]:5Electrical protection class:1CE certificate:100393Solour endering index:80Manual:Download PDE	EAN:	5905963901263	Diffuser type:	MAT
Colour temperature [K]:4000Dimensions (H/W/T/S) [mm]:740/420/320Ingress protection:IP54Impact resistance:IK10Socket type:PL-FRSockets:2Plug type:UNI-SCHUKOWire type:H07RN-3x1,5mm2Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [Im/W]:137Warranty [years]:5Energy efficiency class:1Cable certificate:00393Electrical protection class:1Scentificate:125/2023Solour rendering index:800Manual:Download PDF	Luminous flux [Im]:	33144	Diffuser colour:	white
Ingress protection:IP54Impact resistance:IK10Socket type:PL-FRSockets:2Plug type:UNI-SCHUKOWire type:H07RN-3x1,5mm2Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [Im/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:00393Electrical protection class:1Scentificate:125/2023Solow mendering index:80Manual:Download PDF	Light source:	LED module	Colour of the body:	grey
Socket type:PL-FRSockets:2Plug type:UNI-SCHUKOWire type:HO7RN-3x1,5mm2Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [m/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:000393Electrical protection class:1CE certificate:125/2023Kolume and the state of t	Colour temperature [K]:	4000	Dimensions (H/W/T/S) [mm]:	740/420/320
Plug type:UNI-SCHUKOWire type:HO7RN-3x1,5mm2Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [lm/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:00393Electrical protection class:1Electrificate:125/2023Solow rendering index:80Manual:Download PDF	Ingress protection:	IP54	Impact resistance:	IK10
Supply voltage [V]:230Cable length [m]:5Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [Im/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:000393Electrical protection class:ICE certificate:125/2023Solour rendering index:>80Manual:Download PDF	Socket type:	PL-FR	Sockets:	2
Frequency [Hz]:50Net weight [kg]:7.700Luminous efficacy [lm/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:000393Electrical protection class:ICE certificate:125/2023Colour rendering index:>80Manual:Download PDF	Plug type:	UNI-SCHUKO	Wire type:	H07RN- 3x1,5mm2
Luminous efficacy [Im/W]:137Warranty [years]:5Energy efficiency class:CAdditional accessories:000393Electrical protection class:ICE certificate:125/2023Colour rendering index:>80Manual:Download PDF	Supply voltage [V]:	230	Cable length [m]:	5
Energy efficiency class:CAdditional accessories:000393Electrical protection class:ICE certificate:125/2023Colour rendering index:>80Manual:Download PDF	Frequency [Hz]:	50	Net weight [kg]:	7.700
Electrical protection class: I CE certificate: 125/2023   Colour rendering index: >80 Manual: Download PDF	Luminous efficacy [lm/W]:	137	Warranty [years]:	5
Colour rendering index: >80 Manual: Download PDF	Energy efficiency class:	С	Additional accessories:	000393
	Electrical protection class:	1	CE certificate:	<u>125/2023</u>
<b>SDCM:</b> ≤3	Colour rendering index:	>80	Manual:	Download PDF
	SDCM:	≤ 3		




# **GIANT LED EVO 33000LM GRAY WITH PL-FR SOCKETS**

DETAILED CARD

### **ACCESSORIES AVAILABLE**

index	Name
000300	Adapter plate with click function for mounting the Giant Luminaire on the tripod
000294	Steel tripod 3 m



Steel tripod 3 m (000294)

Card creation date: 23 November 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

A This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 125/2023