
SQ 160 LED PLUS P 2050LM DALI 840 IP44/20 II CL. 75DEG (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	572005
Ingress protection:	IP44/IP20
Impact resistance:	IK08
Nominal power [W]:	17
Luminous flux [lm]*:	2050
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II
Energy efficiency class:	E

CHARACTERISTICS

SQ 160 LED PLUS P is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

SQ 160 LED PLUS P 2050LM DALI 840 IP44/20 II CL. 75DEG (17W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	572005
Nominal power [W]:	17
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	2050
Luminous efficacy [lm/W]:	109
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
Beam angle [°]:	75
Diffuser material:	PC
Diffuser type:	OPAL
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	158/158/78

Mounting dimensions [mm]:	145/145
Impact resistance:	IK08
Ingress protection:	IP44/IP20
Mounting version:	recessed
Working temperature [°C]:	od -20 do +35
Control:	DALI
Net weight [kg]:	0.340
Warranty [years]:	5
Category type:	downlights
LED lifespan L70B50 [h]:	150000
LED lifespan L80B10 [h]:	100000
LED lifespan L90B10 [h]:	50000
DIMM DALI:	yes
CE certificate:	14/2024
Manual:	Download PDF
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Plik LDT:	Download

LIGHT CURVES



SQ 160 LED PLUS P 2050LM DALI 840 IP44/20 II CL. 75DEG (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
998942	Frame square 220 for SQ160 white RAL9016 structure



Frame square 220 for SQ160 white RAL9016 structure (998942)

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 14/2024

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl