

# SQ 160 LED PLUS P 2450LM DALI 840 IP44/20 II CL. MAT (21W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	571916
<b>Ingress protection:</b>	IP44/IP20
<b>Impact resistance:</b>	IK08
<b>Nominal power [W]:</b>	21
<b>Luminous flux [lm]*:</b>	2450
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Electrical protection class:</b>	II
<b>Energy efficiency class:</b>	E

## CHARACTERISTICS

SQ 160 LED PLUS P is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


# SQ 160 LED PLUS P 2450LM DALI 840 IP44/20 II CL. MAT (21W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	571916	Mounting dimensions [mm]:	145/145
Nominal power [W]:	21	Impact resistance:	IK08
Supply voltage [V]:	220 - 240	Ingress protection:	IP44/IP20
Frequency [Hz]:	50 - 60	Mounting version:	recessed
Luminous flux [lm]:	2450	Working temperature [°C]:	od -20 do +35
Luminous efficacy [lm/W]:	111	Control:	DALI
Energy efficiency class:	E	Net weight [kg]:	0.340
Electrical protection class:	II	Warranty [years]:	5
Colour temperature [K]:	4000	Category type:	downlights
Color rendering index (Ra) >:	80	LED lifespan L70B50 [h]:	150000
SDCM:	3	LED lifespan L80B10 [h]:	100000
Power factor:	0.99	LED lifespan L90B10 [h]:	50000
Beam angle [°]:	110	DIMM DALI:	yes
Diffuser material:	PC	CE certificate:	<a href="#">14/2024</a>
Diffuser type:	matt	Manual:	<a href="#">Download PDF</a>
Material of the body:	ABS	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Colour of the body:	white	Pliik LDT:	<a href="#">Download</a>
Dimensions (H/W/T/S) [mm]:	158/158/78		

## LIGHT CURVES



# SQ 160 LED PLUS P 2450LM DALI 840 IP44/20 II CL. MAT (21W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
998942	Frame square 220 for SQ160 white RAL9016 structure



Frame square 220 for SQ160 white  
RAL9016 structure (998942)

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 14/2024