

SQ 160 LED PLUS P 2900LM 840 IP44/20 II CL. PRM (21W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	571954
Ingress protection:	IP44/IP20
Impact resistance:	IK08
Nominal power [W]:	21
Luminous flux [lm]*:	2900
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II
Energy efficiency class:	D

CHARACTERISTICS

SQ 160 LED PLUS P is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.


SQ 160 LED PLUS P 2900LM 840 IP44/20 II CL. PRM (21W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	571954	Colour of the body:	white
Nominal power [W]:	21	Dimensions (H/W/T/S) [mm]:	158/158/78
Supply voltage [V]:	220 - 240	Mounting dimensions [mm]:	145/145
Frequency [Hz]:	50 - 60	Impact resistance:	IK08
Luminous flux [lm]:	2900	Ingress protection:	IP44/IP20
Luminous efficacy [lm/W]:	132	Mounting version:	recessed
Energy efficiency class:	D	Working temperature [°C]:	od -20 do +35
Electrical protection class:	II	Net weight [kg]:	0.300
Colour temperature [K]:	4000	Warranty [years]:	5
Color rendering index (Ra) >:	80	Category type:	downlights
SDCM:	3	LED lifespan L70B50 [h]:	150000
Power factor:	0.99	LED lifespan L80B10 [h]:	100000
Beam angle [°]:	115	LED lifespan L90B10 [h]:	50000
Diffuser material:	PC	CE certificate:	14/2024
Diffuser type:	PRM	Manual:	Download PDF
Material of the body:	ABS	Photobiological safety:	RG0 - exempt (no photobiological hazard)

LIGHT CURVES



SQ 160 LED PLUS P 2900LM 840 IP44/20 II CL. PRM (21W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
998942	Frame square 220 for SQ160 white RAL9016 structure



Frame square 220 for SQ160 white
RAL9016 structure (998942)

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 14/2024