

# RQ 160 LED PLUS N 1800LM DALI 840 IP33 II CL. MAT (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

---

<b>Index:</b>	571701
<b>Ingress protection:</b>	IP33
<b>Impact resistance:</b>	IK08
<b>Nominal power [W]:</b>	17
<b>Luminous flux [lm]*:</b>	1800
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Electrical protection class:</b>	II
<b>Energy efficiency class:</b>	E

## CHARACTERISTICS

---

RQ 160 LED PLUS N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent

## APPLICATION

---

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.


# RQ 160 LED PLUS N 1800LM DALI 840 IP33 II CL. MAT (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	571701	Mounting dimensions [mm]:	117,5
EAN:	5905963571701	Impact resistance:	IK08
Nominal power [W]:	17	Ingress protection:	IP33
Rated power of the luminaire [W]:	19	Mounting version:	surface
Supply voltage [V]:	220 - 240	Working temperature [°C]:	od -20 do +35
Frequency [Hz]:	50 - 60	Control:	DALI
Luminous flux [lm]:	1800	Number on the palette [pcs]:	364
Luminous efficacy [lm/W]:	96	Net weight [kg]:	0.600
Energy efficiency class:	E	Category type:	downlights
Electrical protection class:	II	LED lifespan L70B50 [h]:	132000
Colour temperature [K]:	4000	LED lifespan L80B10 [h]:	84000
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	42000
SDCM:	3	Light distribution type:	lambertian
Power factor:	0.99	DIMM DALI:	yes
Beam angle [°]:	110	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Diffuser material:	PC	Warranty [years]:	5
Diffuser type:	mat	CE certificate:	<a href="#">321/2023</a>
Material of the body:	ABS	PZH certificate:	<a href="#">B-BK-60112-0365/2022</a>
Colour of the body:	white	Manual:	<a href="#">Download PDF</a>
Dimensions (H/W/T/S) [mm]:	166/86	Plik LDT:	<a href="#">Download</a>

## LIGHT CURVES



# RQ 160 LED PLUS N 1800LM DALI 840 IP33 II CL. MAT (17W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 321/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl