RQ 160 LED PLUS N 1900LM DALI 830 IP33 II CL. 75DEG (17W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	571855
Ingress protection:	IP33
Impact resistance:	IK08
Nominal power [W]:	17
Luminous flux [lm]*:	1900
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II
Energy efficiency class:	E

CHARACTERISTICS

RQ 160 LED PLUS N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED PLUS N 1900LM DALI 830 IP33 II CL. 75DEG (17W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	571855
EAN:	5905963571855
Nominal power [W]:	17
Rated power of the luminaire [W]:	19
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	1900
Luminous efficacy [lm/W]:	101
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
Beam angle [°]:	75
Diffuser material:	PC
Diffuser type:	OPAL
Optics:	lens
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	166/86
Mounting dimensions [mm]:	117,5

Impact resistance:	IK08
Ingress protection:	IP33
Mounting version:	surface
Working temperature [°C]:	od -20 do +35
Control:	DALI
Number on the palette [pcs]:	364
Net weight [kg]:	0.500
Category type:	downlights
LED lifespan L70B50 [h]:	150000
LED lifespan L80B10 [h]:	100000
LED lifespan L90B10 [h]:	50000
Light distribution type:	symmetric
DIMM DALI:	yes
Photobiological safety:	RG0 - exempt (no photobiological hazard)
Warranty [years]:	5
CE certificate:	321/2023
PZH certificate:	B-BK-60112-0365/2022
Environmental Product Declaration (EPD):	944/2026
Manual:	Download PDF
ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Plik LDT:	Download

LIGHT CURVES



RQ 160 LED PLUS N 1900LM DALI 830 IP33 II CL. 75DEG (17W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 26 August 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 321/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl