

# RQ 160 LED PLUS N 2050LM 840 IP33 II CL. 75DEG (17W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	571749
<b>Ingress protection:</b>	IP33
<b>Impact resistance:</b>	IK08
<b>Nominal power [W]:</b>	17
<b>Luminous flux [lm]*:</b>	2050
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Electrical protection class:</b>	II
<b>Energy efficiency class:</b>	E

## CHARACTERISTICS

RQ 160 LED PLUS N is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent

## APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

# RQ 160 LED PLUS N 2050LM 840 IP33 II CL. 75DEG (17W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	571749	Dimensions (H/W/T/S) [mm]:	166/86
EAN:	5905963571749	Mounting dimensions [mm]:	117,5
Nominal power [W]:	17	Impact resistance:	IK08
Rated power of the luminaire [W]:	19	Ingress protection:	IP33
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	od -20 do +35
Luminous flux [lm]:	2050	Number on the palette [pcs]:	364
Luminous efficacy [lm/W]:	109	Net weight [kg]:	0.400
Energy efficiency class:	E	Category type:	downlights
Electrical protection class:	II	LED lifespan L70B50 [h]:	150000
Colour temperature [K]:	4000	LED lifespan L80B10 [h]:	100000
Color rendering index (Ra) >:	80	LED lifespan L90B10 [h]:	50000
SDCM:	3	Light distribution type:	lambertian
Power factor:	0.99	Photobiological safety:	RG0 - exempt (no photobiological hazard)
Beam angle [°]:	115	Warranty [years]:	5
Diffuser material:	PC	CE certificate:	<a href="#">321/2023</a>
Diffuser type:	OPAL	PZH certificate:	<a href="#">B-BK-60112-0365/2022</a>
Material of the body:	ABS	Manual:	<a href="#">Download PDF</a>
Colour of the body:	white		

## LIGHT CURVES



# RQ 160 LED PLUS N 2050LM 840 IP33 II CL. 75DEG (17W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
573637	Suspension RQ160 fi100 white ON/OFF. DALI

Card creation date: 12 February 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 321/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl