

RQ 160 LED PLUS P 2600LM 830 IP44/20 II CL. 75DEG (21W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	571657
Ingress protection:	IP44/20
Impact resistance:	IK08
Rated power of the luminaire [W]*:	22
Nominal power [W]:	21
Luminous flux [lm]*:	2600
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	II

CHARACTERISTICS

RQ 160 LED PLUS P is a new line of round luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

RQ 160 LED PLUS P 2600LM 830 IP44/20 II CL. 75DEG (21W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	571657	Dimensions (H/W/T/S) [mm]:	162/70
EAN:	5905963571657	Mounting dimensions [mm]:	ø150
Nominal power [W]:	21	Impact resistance:	IK08
Rated power of the luminaire [W]:	22	Ingress protection:	IP44/20
Supply voltage [V]:	220 - 240	Mounting version:	recessed
Frequency [Hz]:	50 - 60	Working temperature [°C]:	od -20 do +35
Luminous flux [lm]:	2600	Net weight [kg]:	0.300
Luminous efficacy [lm/W]:	118	Category type:	downlights
Energy efficiency class:	D	LED lifespan L70B50 [h]:	132000
Electrical protection class:	II	LED lifespan L80B10 [h]:	84000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	42000
Color rendering index (Ra) >:	80	Photobiological safety:	RG0 - exempt (no photobiological hazard)
SDCM:	3	Warranty [years]:	5
Power factor:	0.99	CE certificate:	322/2023
Beam angle [°]:	75	Manual:	Download PDF
Diffuser material:	PC	PZH certificate:	B-BK-60112-0365/2022
Diffuser type:	OPAL	ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Material of the body:	ABS	Plik LDT:	Download
Colour of the body:	white		

LIGHT CURVES




RQ 160 LED PLUS P 2600LM 830 IP44/20 II CL. 75DEG (21W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
897269	Cover frame for RQ160 D205mm white RAL 9003



Cover frame for RQ160 D205mm white
RAL 9003 (897269)

Card creation date: 26 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 322/2023