



TECHNICAL PARAMETERS

Index:	630231
Ingress protection:	IP20
Nominal power [W]:	25
Luminous flux [lm]*:	2900
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	E
Electrical protection class:	II
Material of the body:	ABS
Diffuser material:	PS

CHARACTERISTICS

Compact LED luminaire designed for suspended installation. Equipped with energy-saving LED GO! panels and an evenly highlighted opal diffuser, providing low glare. Made of plastic.

APPLICATION

This luminaire is designed for indoor use in offices or general utility rooms. It can be used as the main light source and it is particularly well-suited to be used as a light source for workplaces that require eyesight focus. The luminaire is used both in new applications, as well as it can replace traditional fluorescent luminaires with energy-saving LED solutions.

TECHNICAL PARAMETERS TABLE

Nominal power [W]:	25	Mounting version:	suspended
Index:	630231	Working temperature [°C]:	from -20 to +35
Colour temperature [K]:	3000	Cable length [m]:	1
Light source:	LED module	Net weight [kg]:	5.200
Luminous flux [lm]:	2900	EAN:	5905963630231
Energy efficiency class:	E	Category type:	louvres
Rated power of the luminaire [W]:	26.70	CE certificate:	362/2023
Supply voltage [V]:	220-240	SDCM:	≤ 3
Frequency [Hz]:	50 - 60	Power factor:	0.95
Luminous efficacy [lm/W]:	108	PZH certificate:	B-BK-60212-0070/20 B-BK-60212-0042/20
Electrical protection class:	II	LED lifespan L70B50 [h]:	132000
Colour rendering index:	>80	LED lifespan L80B20 [h]:	84000
Beam angle [°]:	120	Manual:	Download PDF
Diffuser material:	PS	LED lifespan L90B10 [h]:	42000
Material of the body:	ABS	ETIM class:	EC001743
Colour of the body:	white	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Dimensions (H/W/T/S) [mm]:	1195/250/69	Warranty [years]:	5
Mounting dimensions [mm]:	980	Plik LDT:	
Ingress protection:	IP20		

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 362/2023