

# INDUSTRY IP66 LED 1450MM 15700LM 840 DALI 70D (106W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Index:</b>	663871
<b>Ingress protection:</b>	IP66
<b>Nominal power [W]:</b>	106
<b>Luminous flux [lm]*:</b>	15700
<b>Colour temperature [K]:</b>	4000
<b>Color rendering index (Ra) &gt;:</b>	80
<b>SDCM:</b>	3
<b>Energy efficiency class:</b>	C
<b>Material of the body:</b>	aluminium
<b>Diffuser material:</b>	glass

## CHARACTERISTICS

INDUSTRY IP66 LED is a hermetic beam from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the luminaire with strength and solidity, and the narrow side profile allows installation in hard to reach places. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 163 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The lampshade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the luminaire with high resistance to harsh environmental conditions.

Suitable for surface and suspended mounting.

Options: any RAL color; diffuser made of PC or PMMA.

## APPLICATION

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.


# INDUSTRY IP66 LED 1450MM 15700LM 840 DALI 70D (106W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	663871	<b>Diffuser colour:</b>	transparent
<b>EAN:</b>	5905963663871	<b>Optics:</b>	lens
<b>Rated power of the luminaire [W]:</b>	115	<b>Optics material:</b>	PMMA
<b>Luminous flux [lm]:</b>	15700	<b>Material of the body:</b>	aluminium
<b>Supply voltage [V]:</b>	220 - 240	<b>Colour of the body:</b>	grey
<b>Frequency [Hz]:</b>	50 - 60	<b>Dimensions (H/W/T/S) [mm]:</b>	1450/63/55
<b>Luminous efficacy [lm/W]:</b>	137	<b>Impact resistance:</b>	IK08
<b>Energy efficiency class:</b>	C	<b>Ingress protection:</b>	IP66
<b>Electrical protection class:</b>	I	<b>Working temperature [°C]:</b>	from -15 to +35
<b>Colour temperature [K]:</b>	4000	<b>DIMM DALI:</b>	yes
<b>Color rendering index (Ra) &gt;:</b>	80	<b>The number of implement units:</b>	1
<b>SDCM:</b>	3	<b>Net weight [kg]:</b>	3.350
<b>LED lifespan L70B50 [h]:</b>	108000	<b>Warranty [years]:</b>	5
<b>LED lifespan L80B10 [h]:</b>	71000	<b>CE certificate:</b>	<a href="#">146/2023</a>
<b>LED lifespan L90B10 [h]:</b>	33000	<b>PZH certificate:</b>	<a href="#">B-BK-60212-0322/20</a>
<b>Beam angle [°]:</b>	70	<b>Manual:</b>	<a href="#">Download PDF</a>
<b>Diffuser material:</b>	glass	<b>Environmental Product Declaration (EPD):</b>	<a href="#">852/2025</a>
<b>Diffuser type:</b>	transparent	<b>Plik LDT:</b>	<a href="#">Download</a>

## LIGHT CURVES




# INDUSTRY IP66 LED 1450MM 15700LM 840 DALI 70D (106W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)



TYTAN LED. ATLAS LED. INDUSTRY  
LED - adjustable handle (set of  
2) (908200)

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 146/2023