INDUSTRY IP66 LED MR 1450MM 46800LM 840 70D (318W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	663932
Ingress protection:	IP66
Impact resistance:	IK08
Nominal power [W]:	318
Luminous flux [lm]*:	46800
Colour temperature [K]:	4000
Energy efficiency class:	D
Material of the body:	aluminium
Colour of the body:	grey
Diffuser material:	glass

CHARACTERISTICS

INDUSTRY IP66 LED MR is a lamp from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the lamp with strength and solidity, as well as steel sheet ensuring installation stability. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 148 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The shade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the lamp with high resistance to harsh environmental conditions. The design of the lamp allows you to adjust the lighting angle of the two extreme modules, so there is the possibility of precise lighting of selected parts of the object. Suitable for suspended mounting. Options: any RAL color.

APPLICATION

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.


INDUSTRY IP66 LED MR 1450MM 46800LM 840 70D (318W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	663932	**Mounting version:**	suspended
EAN:	5905963663932	**Working temperature [°C]:**	from -15 to +35
Light source:	LED module	**Net weight [kg]:**	9.900
Nominal power [W]:	318	**Category type:**	battens
Rated power of the luminaire [W]:	345.90	**AC voltage range [V]:**	198 - 264
Supply voltage [V]:	220 - 240	**DC voltage range [V]:**	176 - 280
Frequency [Hz]:	50 - 60	**LED lifespan L70B50 [h]:**	108000
Luminous flux [lm]:	46800	**LED lifespan L80B10 [h]:**	71000
Luminous efficacy [lm/W]:	135	**LED lifespan L90B10 [h]:**	33000
Energy efficiency class:	D	**Power factor:**	0.98
Electrical protection class:	I	**Surge protection [kV]:**	2
Colour temperature [K]:	4000	**Optics material:**	PC
Color rendering index (Ra) >:	80	**Optics:**	lens
SDCM:	3	**The number of implement units:**	3
Diffuser material:	glass	**Warranty [years]:**	5
Material of the body:	aluminium	**CE certificate:**	148/2023
Colour of the body:	grey	**Manual:**	Download PDF
Dimensions (H/W/T/S) [mm]:	1450/205/125	**Environmental Product Declaration (EPD):**	852/2025
Impact resistance:	IK08	**Plik LDT:**	Download
Ingress protection:	IP66		

TECHNICAL DETAILS



INDUSTRY IP66 LED MR 2

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 148/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl