

INDUSTRY IP66 LED 570MM 3500LM 840 DALI (23W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	552793
Ingress protection:	IP66
Nominal power [W]:	23
Luminous flux [lm]*:	3500
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
Energy efficiency class:	C
Material of the body:	aluminium
Diffuser material:	glass

CHARACTERISTICS

INDUSTRY IP66 LED is a hermetic beam from the NEXT GEN line, which is a new generation of lamps dedicated to LED technology. The body, made from scratch, made of aluminum profile and subjected to anodization process, provides the luminaire with strength and solidity, and the narrow side profile allows installation in hard to reach places. LEDs from a reputable manufacturer and new LED modules have an impact on very high luminous efficacy: up to 163 lm / W. This guarantees that the required lighting level is achieved and that significant energy savings are achieved. The lampshade is made of UV resistant tempered glass. The combination of materials (aluminum and toughened glass) and a non-dismantled construction with an external connector provides the luminaire with high resistance to harsh environmental conditions.

Suitable for surface and suspended mounting.

Options: any RAL color; diffuser made of PC or PMMA.

APPLICATION

The multi-purpose LED luminaire has been designed for use in areas requiring high dust and water resistance. It is especially recommended for use in rooms intended for medical and laboratory purposes as well as in industrial premises.


INDUSTRY IP66 LED 570MM 3500LM 840 DALI (23W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	552793	Diffuser type:	transparent
EAN:	5905963552793	Material of the body:	aluminium
Rated power of the luminaire [W]:	23	Colour of the body:	grey
Luminous flux [lm]:	3500	Dimensions (H/W/T/S) [mm]:	570/63/55
Supply voltage [V]:	220 - 240	Impact resistance:	IK08
Frequency [Hz]:	50 - 60	Ingress protection:	IP66
Luminous efficacy [lm/W]:	152	Working temperature [°C]:	from -20 to +35
Energy efficiency class:	C	DIMM DALI:	yes
Electrical protection class:	I	The number of implement units:	1
Colour temperature [K]:	4000	Control:	DALI
Color rendering index (Ra) >:	80	Net weight [kg]:	1.300
SDCM:	3	Warranty [years]:	5
LED lifespan L70B50 [h]:	108000	CE certificate:	145/2023
LED lifespan L80B10 [h]:	71000	PZH certificate:	B-BK-60212-0322/20
LED lifespan L90B10 [h]:	33000	Manual:	Download PDF
Beam angle [°]:	110	Environmental Product Declaration (EPD):	852/2025
Diffuser material:	glass	Plik LDT:	Download

LIGHT CURVES




INDUSTRY IP66 LED 570MM 3500LM 840 DALI (23W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)



TYTAN LED. ATLAS LED. INDUSTRY
LED - adjustable handle (set of
2) (908200)

Card creation date: 16 December 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 145/2023