TIARA LED L PRO 5775LM 730 RM3 IP66 I CL. DALI (35W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	923258
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	35
Luminous flux [lm]*:	5775
Colour temperature [K]:	3000
Colour rendering index:	> 70
Electrical protection class:	I
Optics:	RM3
Control:	Yes + 5-stage power reduction

CHARACTERISTICS

TIARA LED PRO a family of LED road luminaires based on a proven form factor. It uses directional multi-lens matrices, made of PMMA, with each lens having the same optics, ensuring that the luminous characteristics remain constant over time. Components from renowned manufacturers and new LED panels contribute to the very high luminous efficacy achieved at the output of the luminaire - reaching 170 lm/W. The two-chamber construction of the luminaire maintains the tightness of the optical chamber during assembly work and allows tool-free access to the electrical equipment chamber. The upper part of the luminaire, has dedicated hinges and a safety cord. Using standard tools, quick and convenient servicing is possible, allowing the replacement of any component without having to dismantle the entire luminaire and make soldered connections. The body and handle are made of die-cast aluminium, powder-coated grey, and have a very high IP66 protection rating and IK09 mechanical impact resistance. Standard features: ergonomic light module suspension system; fully programmable DALI driver; CLO constant lumen maintenance and autonomous 5-stage power reduction functions available; NTC overheating protection; filter to prevent condensation; connection terminals; tool-free access. Additional options: NEMA, ZHAGA connectors; interfacing with control systems, RCR motion sensor; additional SP10kV protection outside the power supply, on/off power supply without power reduction function; knife disconnector to disconnect voltage if the electrical compartment is opened; design with cable terminated with quick disconnect; painting in any RAL colour. Certifications: CE, RoHS, ENEC, ENEC+, Zhaga D4i.

APPLICATION

Thanks to the use of dedicated optics, it is possible to illuminate objects such as: motorways, motorways, national roads, voivodeships, districts, communes, municipalities, housing estates, area lighting. Optics are also available to illuminate: pedestrian crossings, pavements and cycle paths.

TIARA LED L PRO 5775LM 730 RM3 IP66 I CL. DALI (35W)


DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	923258
EAN:	5905963923258
ETIM class:	EC000062
Category type:	street lighting
Version:	L
Light source:	LED module
Rated power of the luminaire [W]:	35
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	5775
Luminous efficacy [lm/W]:	165
Energy efficiency class:	B
Electrical protection class:	I
Colour temperature [K]:	3000
Colour rendering index:	> 70
SDCM:	≤ 5
Power factor:	0.95
Surge protection [kV]:	10
Diffuser material:	toughened glass
Diffuser type:	transparent
Optics material:	PMMA
Optics:	RM3

Exchangeable source:	yes
Material of the body:	powder coated aluminium
Colour of the body:	grey
Dimensions (H/W/T/S) [mm]:	870/262/122
Mounting dimensions [mm]:	ø60
Impact resistance:	IK09
Ingress protection:	IP66
Mounting version:	Top, on pole / Side, on boom
Beam angle adjustment [°]:	-5 to +15 (peak); -15 to +5 (side)
Lateral surface (SCx) [m2]:	0.034
Working temperature [°C]:	from -40 to +50
LED lifespan L90B10 [h]:	100000
DIMM DALI:	yes
Control:	Yes + 5-stage power reduction
Protection type:	NTC
Net weight [kg]:	6.500
Warranty [years]:	10
ULOR:	0%
ENEC Certificate:	0228/ENEC/20/M1. 0065/ENEC+/21/M1
CE certificate:	63/2023
Manual:	Download PDF

LIGHT CURVES




TIARA LED L PRO 5775LM 730 RM3 IP66 I CL. DALI (35W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
314049	wall holder (galvanized)
314056	wall holder (grey)
UL00184	mounting grip 78 mm TIARA LED



wall holder (galvanized) (314049)



wall holder (grey) (314056)



mounting grip 78 mm TIARA LED (UL00184)

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 63/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl