

TECHNICAL PARAMETERS

Ingress protection: IP65

Nominal power [W]:

Luminous flux [lm]*: 130

Colour temperature [K]: 5000

Electrical protection class:

Material of the body: PC

Mounting version: surface

CNBOP certificate: 4958/2023

Warranty [years]: 2 / 0.5 (bateria)

Energy efficiency class: D

CHARACTERISTICS

Surface-mounted autonomous emergency luminaire with integrated, energy-saving LED light panel. Body made of polycarbonate (PC). Optical system available in 3 variants: basic, corridor, open space. Luminaire is fitted with batteries with 1h, 2h or 3h emergency operation time. The luminaire is using Ni-Mh or Ni-Cd battery with voltage of 3.6V and 24 hours of full charge with manual or automatic test function (AT).

APPLICATION

Autonomous emergency luminaire is mainly used for illumination of escape routes and fire protection devices after power failure, i.e. in emergency mode. Especially recommended everywhere, where it is necessary to install emergency lighting within the scope of modernization of existing system. Successfully replaces luminaires with embedded emergency module. Due to additional sealing, the luminaire achieves IP65 tightness and may be used in places with increased humidity or outdoors under the roofing.




TECHNICAL PARAMETERS TABLE

Light source:	LED module
Nominal power [W]:	1
	·
Rated power of the luminaire [W]:	1
Supply voltage [V]:	220-240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	130
Luminous efficacy [lm/W]:	134
Electrical protection class:	II
Colour temperature [K]:	5000
Color rendering index (Ra) >:	70
LED lifespan L70B50 [h]:	275000
Beam angle [°]:	120
Battery:	NiMh
Diffuser material:	PMMA
Material of the body:	PC
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	ø140/40
Mounting dimensions [mm]:	104
Ingress protection:	IP65
	•

	•	
Impact resistance:	IK07	
Mounting version:	surface	
Working temperature [°C]:	from +5 to +35	
Emergency lighting [h]:	2	
Index:	550089	
EAN:	5905963550089	
Category type:	emergency lighting	
Version:	general	
Autotest:	yes	
Operating mode:	NM	
Light distribution type:	general	
ETIM class:	EC001957	
Photobiological safety:	RG0 - exempt (no photobiological hazard)	
Luminaire rated power 0min [W]:	1	
Energy efficiency class:	D	
Warranty [years]:	2 / 0.5 (bateria)	
CE certificate:	112/2023	
Manual:	Download PDF	
Plik LDT:	Download	

LIGHT CURVES






ACCESSORIES AVAILABLE


•	
index	Name
545672	DOT CS galvanized steel arm
551161	Ceiling spacer DOT white matt
997570	DOT square frame. white matt texture
997587	DOT square frame black matt texture








Ceiling spacer DOT white matt (551161)



DOT square frame. white matt texture (997570)



DOT square frame black matt texture (997587)

