

# OPRAWA MASZYNOWA TYPE 101 LED 14W PC EVO 24V 1255MM CABLE LENGTH 5M CEE1750LM 4000K

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |            |
|------------------------------------|------------|
| Light source:                      | LED module |
| Rated power of the luminaire [W]*: | 14         |
| Colour temperature [K]:            | 4000       |
| Luminous efficacy [lm/W]:          | 126        |
| Supply voltage [V]:                | DC 24      |
| Electrical protection class:       | III        |
| Energy efficiency class:           | D          |
| Colour rendering index:            | 80         |

## CHARACTERISTICS

- Power: 13W, 14W, 26W or 40W
- Light source: LED
- High ingress protection class IP54
- Made of painted frozen polycarbonate
- Designed for series connecting

## APPLICATION

Thanks to its various functions, the lamp is ideal for illuminating car lifts, ducts, machines, workplaces, etc. High luminous flux and maximum degree of impact resistance are especially important for lighting the workplace. High degree of tightness allows for its use in the most difficult weather conditions. Numerous accessories provide a wide range of mounting possibilities so as to precisely direct the light beam leaving the worker's hands free.

# OPRAWA MASZYNOWA TYPE 101 LED 14W PC EVO 24V

## 1255MM CABLE LENGTH 5M CEE1750LM 4000K

DETAILED CARD

### TECHNICAL PARAMETERS TABLE

|                                   |            |                       |                              |
|-----------------------------------|------------|-----------------------|------------------------------|
| Light source:                     | LED module | Diffuser material:    | PC                           |
| Rated power of the luminaire [W]: | 14         | Diffuser type:        | transparent                  |
| Supply voltage [V]:               | DC 24      | Material of the body: | sheet steel + PC             |
| Luminous flux [lm]:               | 1737       | Impact resistance:    | IK10                         |
| Energy efficiency class:          | D          | Ingress protection:   | IP54                         |
| Electrical protection class:      | III        | Wire type:            | H05RN-F                      |
| Colour temperature [K]:           | 4000       | Net weight [kg]:      | 2.130                        |
| Colour rendering index:           | 80         | Warranty [years]:     | 5                            |
| SDCM:                             | ≤ 3        | CE certificate:       | <a href="#">284/2023</a>     |
| Power factor:                     | 0.95       | Manual:               | <a href="#">Download PDF</a> |
| LED lifespan L70B50 [h]:          | 100000     | Index:                | 888786                       |
| Beam angle [°]:                   | 120        | EAN:                  | 5905963888786                |

# OPRAWA MASZYNOWA TYPE 101 LED 14W PC EVO 24V 1255MM CABLE LENGTH 5M CEE1750LM 4000K

DETAILED CARD

## ACCESSORIES AVAILABLE

| index  | Name                                  |
|--------|---------------------------------------|
| 899140 | Mounting holder for the TYPE 101 lamp |



Mounting holder for the TYPE 101  
lamp (899140)

Card creation date: 09 November 2023  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 284/2023