SQ 100 LED PLUS P 590LM MAT II CL. IP44/20 830 (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP44/20
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	590
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	matt

CHARACTERISTICS

SQ 100 LED PLUS P is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Recessed-mounted luminaire with the possibility of flush mounting in modular ceilings and in plasterboard ceilings (using plasterboard recessing kit) is especially recommended for offices, spacious corridors and public spaces.

SQ 100 LED PLUS P 590LM MAT II CL. IP44/20 830 (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	572579
EAN:	5905963572579
Rated power of the luminaire [W]:	6
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [lm]:	590
Luminous efficacy [lm/W]:	102
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Power factor:	0.99
Beam angle [°]:	105
Diffuser material:	PC
Diffuser type:	matt
Diffuser colour:	milky

Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	102/102/75
Impact resistance:	IK08
Ingress protection:	IP44/20
Mounting version:	recessed
Working temperature [°C]:	from -25 to +35
Net weight [kg]:	0.300
LED lifespan L70B50 [h]:	150000
LED lifespan L80B10 [h]:	100000
LED lifespan L90B10 [h]:	50000
Warranty [years]:	5
CE certificate:	313/2023
Environmental Product Declaration (EPD):	944/2026
Manual:	Download PDF
ISO Certificates:	9001:2015. 14001:2015. 45001:2018. 50001:2018
Plik LDT:	Download

Card creation date: 04 May 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 313/2023

LENA LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl