


# SQ 100 LED PLUS N 590LM MAT II CL. IP33 830 (6W)

DETAILED CARD



## TECHNICAL PARAMETERS

|                                    |       |
|------------------------------------|-------|
| Ingress protection:                | IP33  |
| Rated power of the luminaire [W]*: | 6     |
| Luminous flux [lm]*:               | 590   |
| Colour temperature [K]:            | 3000  |
| Colour rendering index:            | 80    |
| Energy efficiency class:           | E     |
| Material of the body:              | ABS   |
| Colour of the body:                | white |
| Diffuser material:                 | PC    |
| Diffuser type:                     | matt  |

## CHARACTERISTICS

SQ 100 LED PLUS N is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

## APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.

# SQ 100 LED PLUS N 590LM MAT II CL. IP33 830 (6W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|                                   |               |                            |                              |
|-----------------------------------|---------------|----------------------------|------------------------------|
| Index:                            | 572654        | Material of the body:      | ABS                          |
| EAN:                              | 5905963572654 | Colour of the body:        | white                        |
| Rated power of the luminaire [W]: | 6             | Dimensions (H/W/T/S) [mm]: | 108/108/85                   |
| Supply voltage [V]:               | 220 - 240     | Impact resistance:         | IK08                         |
| Frequency [Hz]:                   | 50 - 60       | Ingress protection:        | IP33                         |
| Luminous flux [lm]:               | 590           | Mounting version:          | surface                      |
| Luminous efficacy [lm/W]:         | 95            | Working temperature [°C]:  | from -25 to +35              |
| Energy efficiency class:          | E             | Net weight [kg]:           | 0.350                        |
| Electrical protection class:      | II            | CE certificate:            | <a href="#">312/2023</a>     |
| Colour temperature [K]:           | 3000          | Warranty [years]:          | 5                            |
| Colour rendering index:           | 80            | Warranty [years]:          | 5                            |
| SDCM:                             | ≤ 3           | Manual:                    | <a href="#">Download PDF</a> |
| Power factor:                     | 0.99          | LED lifespan L70B50 [h]:   | 132000                       |
| Beam angle [°]:                   | 105           | LED lifespan L80B20 [h]:   | 84000                        |
| Diffuser material:                | PC            | LED lifespan L90B10 [h]:   | 42000                        |
| Diffuser type:                    | matt          | Plik LDT:                  | <a href="#">Download</a>     |
| Diffuser colour:                  | milky         |                            |                              |

Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 312/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)