
SQ 100 LED PLUS N 590LM MAT II CL. IP33 830 (6W)

DETAILED CARD





TECHNICAL PARAMETERS

Ingress protection:	IP33
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	590
Colour temperature [K]:	3000
Colour rendering index:	>80
Energy efficiency class:	Е
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	MAT

CHARACTERISTICS

SQ 100 LED PLUS N is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.



SQ 100 LED PLUS N 590LM MAT II CL. IP33 830 (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

	I
Index:	572654
EAN:	5905963572654
Rated power of the luminaire [W]:	6
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous flux [Im]:	590
Luminous efficacy [lm/W]:	95
Energy efficiency class:	E
Electrical protection class:	II
Colour temperature [K]:	3000
Colour rendering index:	>80
SDCM:	≤3
Power factor:	0.99
Beam angle [°]:	105
Diffuser material:	PC
Diffuser type:	MAT

Diffuser colour:	milky
Material of the body:	ABS
Colour of the body:	white
Dimensions (H/W/T/S) [mm]:	108/108/85
Impact resistance:	IK08
Ingress protection:	IP33
Mounting version:	surface
Working temperature [°C]:	from -25 to +35
Net weight [kg]:	0.350
CE certificate:	312/2023
Warranty [years]:	5
Warranty [years]:	5
Manual:	Download PDF
LED lifespan L70B50 [h]:	132000
LED lifespan L80B20 [h]:	84000
LED lifespan L90B10 [h]:	42000

Card creation date: 24 February 2021

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

