


SQ 100 LED PLUS N 630LM MAT II CL. IP33 840 (6W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP33
Rated power of the luminaire [W]*:	6
Luminous flux [lm]*:	630
Colour temperature [K]:	4000
Colour rendering index:	>80
Energy efficiency class:	E
Material of the body:	ABS
Colour of the body:	white
Diffuser material:	PC
Diffuser type:	MAT

CHARACTERISTICS

SQ 100 LED PLUS N is a new line of square luminaires. The construction, designed from scratch, introduces new solutions ensuring excellent lighting parameters. The body is made of plastic, therefore it is characterized by low weight. The diffuser provides excellent light transmission. The integrated LED module guarantees low power consumption and all the advantages of modern LED light sources.

APPLICATION

Surface-mounted luminaire is especially recommended for offices, spacious corridors and public spaces.


SQ 100 LED PLUS N 630LM MAT II CL. IP33 840 (6W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	572630	Material of the body:	ABS
Rated power of the luminaire [W]:	6	Colour of the body:	white
EAN:	5905963572630	Dimensions (H/W/T/S) [mm]:	108/108/85
Colour temperature [K]:	4000	Impact resistance:	IK08
Luminous flux [lm]:	630	Ingress protection:	IP33
Energy efficiency class:	E	Mounting version:	surface
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -25 to +35
Frequency [Hz]:	50 - 60	Net weight [kg]:	0.350
Luminous efficacy [lm/W]:	102	CE certificate:	312/2023
Electrical protection class:	II	Warranty [years]:	5
Colour rendering index:	>80	Warranty [years]:	5
SDCM:	≤ 3	Manual:	Download PDF
Power factor:	0.99	LED lifespan L70B50 [h]:	132000
Beam angle [°]:	105	LED lifespan L80B20 [h]:	84000
Diffuser material:	PC	LED lifespan L90B10 [h]:	42000
Diffuser type:	MAT	Plik LDT:	Download
Diffuser colour:	milky		

LIGHT CURVES



Card creation date: 09 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 312/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl