



TECHNICAL PARAMETERS

Index:	550607
Ingress protection:	IP65/20
Luminous flux [lm]*:	130
Colour temperature [K]:	5000
Material of the body:	PC
Emergency lighting [h]:	2
Battery:	NiMh
Operating mode:	NM
Mounting version:	recessed

CHARACTERISTICS

Recessed mounted autonomous emergency luminaire with integrated, energy-saving LED module. Body made of polycarbonate (PC). Optical system available in 3 variants: basic, corridor, open space. Luminaire is fitted with batteries with 1h, 2h or 3h emergency operation time. The luminaire is using Ni-Mh or Ni-Cd battery with voltage of 3.6V and 24 hours of full charge with manual or automatic test function (AT).

Available versions:

M – maintained,
NM- non-maintained,
AT – autotest.

APPLICATION

Emergency luminaire, used mainly for illumination of escape routes and fire protection devices after power failure, i.e. in emergency lighting mode. Depending on the optical system used, the luminaire may illuminate: escape routes (in corridor light distribution mode) or be used as anti-panic lighting (in standard light distribution mode or open space light distribution mode). Open Space light distribution mode is dedicated to openoffice space of lesser height.

TECHNICAL PARAMETERS TABLE

Index:	550607	Dimensions (H/W/T/S) [mm]:	ø135/30
EAN:	5905963550607	Mounting dimensions [mm]:	ø100
Light source:	LED module	Ingress protection:	IP65/20
Nominal power [W]:	1	Mounting version:	recessed
Rated power of the luminaire [W]:	1	Working temperature [°C]:	from +5 to +35
Supply voltage [V]:	220-240	Emergency lighting [h]:	2
Frequency [Hz]:	50 - 60	Net weight [kg]:	0.430
Luminous flux [lm]:	130	Category type:	emergency lighting
Luminous efficacy [lm/W]:	134	Version:	general
Electrical protection class:	I	Operating mode:	NM
Energy efficiency class:	D	Light distribution type:	general
Colour temperature [K]:	5000	ETIM class:	EC001957
Colour rendering index:	>70	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L70B50 [h]:	275000	Luminaire rated power 0min [W]:	1
Beam angle [°]:	120	Warranty [years]:	2 / 0.5 (bateria)
Battery:	NiMh	Warranty [years]:	2 / 0.5 (battery)
Diffuser material:	PMMA	CE certificate:	77/2023
Material of the body:	PC	Manual:	Download PDF
Colour of the body:	white		

LIGHT CURVES

