

BARIS 40 LED N 4200LM UGR I CL. IP20 1421 MM 840 ANODE CO 34W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	459665
Rated power of the luminaire [W]*:	34
Luminous flux [lm]*:	4200
Colour temperature [K]:	4000
Ingress protection:	IP20
UGR (4H8H):	16.8 - 18.8
Energy efficiency class:	D
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	transparent

CHARACTERISTICS

Luminaires BARIS 40 LED UGR was created to provide maximum comfort and efficiency. A UGR (Unified Glare Rating) of less than 19 minimizes the effect of glare affecting well-being, reducing fatigue and fewer mistakes.

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED N 4200LM UGR I CL. IP20 1421 MM 840 ANODE CO 34W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	459665	Diffuser colour:	transparent
EAN:	5905963459665	Optics:	raster UGR
Rated power of the luminaire [W]:	34	Material of the body:	aluminium
Luminous flux [lm]:	4200	Colour of the body:	grey
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	53/40/1421
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous efficacy [lm/W]:	122	Mounting version:	surface
Energy efficiency class:	D	Net weight [kg]:	1.510
Electrical protection class:	I	UGR (4H8H):	16.8 - 18.8
Colour temperature [K]:	4000	Warranty [years]:	5
Colour rendering index:	>80	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
SDCM:	≤ 3	Warranty [years]:	5
LED lifespan L70B50 [h]:	109000	CE certificate:	239/2023
LED lifespan L80B20 [h]:	69000	ENEC Certificate:	PL BBJ/003/2022/M1/A1
LED lifespan L90B10 [h]:	34000	Manual:	Download PDF
Diffuser material:	PMMA	Impact resistance:	IK03
Diffuser type:	transparent		

LIGHT CURVES



Card creation date: 09 July 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE).

Certificate CE - Nr: 239/2023

LENA
LIGHTING

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl