

BARIS 40 LED Z 3300LM UGR DALI I CL. IP20 1140 MM 840 BLACK 27W

DETAILED CARD



TECHNICAL PARAMETERS

Index:	459283
Rated power of the luminaire [W]*:	27
Luminous flux [lm]*:	3300
Colour temperature [K]:	4000
Ingress protection:	IP20
UGR (4H8H):	16.8 - 18.7
Energy efficiency class:	D
Material of the body:	aluminium
Diffuser material:	PMMA
Diffuser type:	transparent

CHARACTERISTICS

Luminaires BARIS 40 LED UGR was created to provide maximum comfort and efficiency. A UGR (Unified Glare Rating) of less than 19 minimizes the effect of glare affecting well-being, reducing fatigue and fewer mistakes.

Suspended or surface-mounted luminaire with a very narrow cross-section. The bodies are available as an anodised aluminium profile in grey or as an aluminium profile painted in white or black (other colours available on request). Optical system in the form of an opal cover. The luminaire is equipped with a unique suspension system that facilitates mounting and adjustment of the suspension length. All BARIS 40 LED suspended luminaires have 1.2m long slings in a set with a box.

APPLICATION

The luminaire is intended for indoor use. Especially recommended as a source of main lighting conducive to office work. Unique design, energy-saving LED modules and possible integration with external lighting control systems in the DALI standard make this luminaire suitable for use in modern A+ class office buildings, with particular emphasis on representative rooms.

BARIS 40 LED Z 3300LM UGR DALI I CL. IP20 1140 MM 840 BLACK 27W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	459283	LED lifespan L80B20 [h]:	69000
Rated power of the luminaire [W]:	27	LED lifespan L90B10 [h]:	34000
EAN:	5905963459283	Diffuser material:	PMMA
Colour temperature [K]:	4000	Diffuser type:	transparent
Luminous flux [lm]:	3300	Diffuser colour:	transparent
Colour of the body:	black	Optics:	raster UGR
Supply voltage [V]:	220 - 240	Material of the body:	aluminium
DIMM DALI:	yes	Net weight [kg]:	1.690
Frequency [Hz]:	50 - 60	UGR (4H8H):	16.8 - 18.7
Ingress protection:	IP20	Warranty [years]:	5
Energy efficiency class:	D	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Luminous efficacy [lm/W]:	121	Warranty [years]:	5
Mounting version:	suspended	CE certificate:	238/2023
Dimensions (H/W/T/S) [mm]:	53/40/1140	ENEC Certificate:	PL BBJ/003/2022/M1/A1
Electrical protection class:	I	Manual:	Download PDF
Colour rendering index:	>80	Impact resistance:	IK03
SDCM:	≤ 3	Plik LDT:	Download
LED lifespan L70B50 [h]:	109000		

LIGHT CURVES



Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 238/2023



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl