

QUEST 2 LED M 11000LM I CL. IP66 830 SP10KV (82W)

DETAILED CARD



TECHNICAL PARAMETERS

Index:	699214
Ingress protection:	IP66
Impact resistance:	IK09
Rated power of the luminaire [W]*:	82
Luminous flux [lm]*:	11000
Colour temperature [K]:	3000
Color rendering index (Ra) >:	80
SDCM:	3
Electrical protection class:	I
Energy efficiency class:	D

CHARACTERISTICS

High-quality floodlight with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass. It is equipped with directional lens matrices with 3 different light distributions: symmetrical (120°), asymmetric narrow ASN and asymmetric wide ASW. Non-corrosive mounting bracket allowing for adjustment angles between -140° to +185°. The luminaire is available in 2 sizes: M and L. Standard equipped with 0.1m long H07RN-F cable and IP66 quick connector. Wide range of accessories available: protective net, grip for the lighting pole, wall bracket.

APPLICATION

The fitting is dedicated for lighting elevations and billboards.


QUEST 2 LED M 11000LM I CL. IP66 830 SP10KV (82W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	699214	Dimensions (H/W/T/S) [mm]:	321/424/37
Light source:	LED	Impact resistance:	IK09
Rated power of the luminaire [W]:	82	Ingress protection:	IP66
Supply voltage [V]:	220 - 240	Mounting version:	surface
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous flux [lm]:	11000	Lateral surface (SCx) [m2]:	0.140
Luminous efficacy [lm/W]:	134	Net weight [kg]:	4.200
Energy efficiency class:	D	LED lifespan L70B50 [h]:	125000
Electrical protection class:	I	LED lifespan L80B20 [h]:	79000
Colour temperature [K]:	3000	LED lifespan L90B10 [h]:	38000
Color rendering index (Ra) >:	80	Cable length [m]:	0.90
SDCM:	3	Mark D:	yes
Beam angle [°]:	120	Additional accessories:	protective grid, pole mount, wall mount
Surge protection [kV]:	10	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Diffuser material:	glass	Warranty [years]:	5
Diffuser type:	transparent	CE certificate:	86/2021
Material of the body:	aluminium	PZH certificate:	B-BK-60212-0480/21
Colour of the body:	anthracite grey	Environmental Product Declaration (EPD):	816/2025
The number of implement units:	1	Manual:	Download PDF
Version:	M	Plik LDT:	Download

LIGHT CURVES




QUEST 2 LED M 11000LM | CL. IP66 830 SP10KV (82W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
559938	QUEST PLUS LED M/L wall holder RAL9006
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016
965913	QUEST 2 LED M/L MAX wall mount RAL7016
567728	QUEST 2 LED M/L Pole holder




QUEST PLUS LED M/L wall holder
RAL9006 (559938)




QUEST 2 LED M - recessed frame (699993)




QUEST 2 LED L - recessed frame (699986)




QUEST 2 LED L protective grid
RAL7016 (699962)



QUEST 2 LED M protective grid
RAL7016 (699979)



QUEST 2 LED M/L MAX wall mount
RAL7016 (965913)



QUEST 2 LED M/L Pole
holder (567728)

Card creation date: 28 October 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric and electronic waste equipment regulations (WEEE). Certificate CE - Nr: 86/2021