

QUEST 2 LED HB NT M 14200LM RCR I CL. IP66 840 70D SP10KV (108W)

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK09
Rated power of the luminaire [W]*:	108
Luminous flux [lm]*:	14200
Colour temperature [K]:	4000
Colour rendering index:	> 80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium

CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

QUEST 2 LED HB NT M 14200LM RCR I CL. IP66 840 70D SP10KV (108W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Rated power of the luminaire [W]:	108	Impact resistance:	IK09
Index:	698644	Motion sensor:	yes
Colour temperature [K]:	4000	Ingress protection:	IP65
Luminous flux [lm]:	14200	Working temperature [°C]:	from -20 to +35
Beam angle [°]:	70	Version:	1xM
Supply voltage [V]:	220 - 240	Lateral surface (SCx) [m2]:	0.140
Frequency [Hz]:	50 - 60	Mounting version:	surface
Luminous efficacy [lm/W]:	131	Mark D:	yes
Energy efficiency class:	D	Net weight [kg]:	4.200
Electrical protection class:	I	Warranty [years]:	5
Colour rendering index:	> 80	Light distribution type:	70 UGR<22
SDCM:	≤ 3	Efficiency of the luminaire:	0.86
LED lifespan L70B50 [h]:	125000	Additional accessories:	protective grid
LED lifespan L80B20 [h]:	79000	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
LED lifespan L90B10 [h]:	38000	Cable length [m]:	0.90
Surge protection [kV]:	10	The number of implement units:	1
Diffuser material:	glass	Warranty [years]:	5
Diffuser type:	transparent	CE certificate:	158/2023
Optics:	lens	PZH certificate:	B-BK-60212-0480/21
Material of the body:	aluminium	Manual:	Download PDF
Colour of the body:	anthracite grey	Plik LDT:	Download
Dimensions (H/W/T/S) [mm]:	321/424/37		

LIGHT CURVES



QUEST 2 LED HB NT M 14200LM RCR I CL. IP66 840 70D SP10KV (108W)

DETAILED CARD

ACCESSORIES AVAILABLE

index	Name
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699948	QUEST 2 LED HB L protective grid RAL7016 single suspension
699955	QUEST 2 LED HB M protective grid RAL7016 single suspension
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016



QUEST 2 LED M - recessed
frame (699993)



QUEST 2 LED L - recessed
frame (699986)



QUEST 2 LED L protective grid
RAL7016 (699962)



QUEST 2 LED M protective grid
RAL7016 (699979)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 158/2023