

# QUEST 2 LED HB NT M 28400LM RCR I CL. IP66 840 70D SP10KV (216W)

DETAILED CARD



## TECHNICAL PARAMETERS

Ingress protection:	IP65
Impact resistance:	IK09
Rated power of the luminaire [W]*:	216
Luminous flux [lm]*:	28400
Colour temperature [K]:	4000
Colour rendering index:	80
SDCM:	≤ 3
Electrical protection class:	I
Energy efficiency class:	D
Material of the body:	aluminium

## CHARACTERISTICS

High-quality highbay with inbuilt LED source. The body is made of die-cast aluminium, powder coated in anthracite grey (RAL 7016), and the mounting bracket is made of black-painted steel. The diffuser is made of 5 mm thick tempered glass.

Available version with radio motion sensor:

- allowing additional savings in electricity consumption
- convenient change of parameters by remote control (to be purchased separately).

## APPLICATION

The luminaire is dedicated for surface or suspended installation (with chains) for both internal and external use. It is designed for industrial plants, production halls and large area warehouses.

# QUEST 2 LED HB NT M 28400LM RCR I CL. IP66 840 70D SP10KV (216W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE


Index:	698651	Dimensions (H/W/T/S) [mm]:	671/424/37
Rated power of the luminaire [W]:	216	Impact resistance:	IK09
Luminous flux [lm]:	28400	Ingress protection:	IP65
Supply voltage [V]:	220 - 240	Working temperature [°C]:	from -20 to +35
Frequency [Hz]:	50 - 60	Lateral surface (SCx) [m2]:	0.280
Luminous efficacy [lm/W]:	131	Motion sensor:	yes
Energy efficiency class:	D	The number of implement units:	2
Electrical protection class:	I	Mark D:	yes
Colour temperature [K]:	4000	Net weight [kg]:	8.600
Colour rendering index:	80	Version:	2xM
SDCM:	≤ 3	Light distribution type:	70 UGR<22
LED lifespan L70B50 [h]:	125000	Efficiency of the luminaire:	0.86
LED lifespan L80B20 [h]:	79000	Additional accessories:	protective grid
LED lifespan L90B10 [h]:	38000	Cable length [m]:	0.90
Beam angle [°]:	70	Photobiological safety:	Risk Group 1 (no photobiological hazard under normal behavioral limitation)
Surge protection [kV]:	10	Warranty [years]:	5
Diffuser material:	glass	CE certificate:	<a href="#">158/2023</a>
Diffuser type:	transparent	PZH certificate:	<a href="#">B-BK-60212-0480/21</a>
Optics:	lens	Environmental Product Declaration (EPD):	<a href="#">816/2025</a>
Material of the body:	aluminium	Manual:	<a href="#">Download PDF</a>
Colour of the body:	anthracite grey	Plik LDT:	<a href="#">Download</a>

# QUEST 2 LED HB NT M 28400LM RCR I CL. IP66 840 70D SP10KV (216W)


DETAILED CARD

## ACCESSORIES AVAILABLE


index	Name
699993	QUEST 2 LED M - recessed frame
699986	QUEST 2 LED L - recessed frame
699948	QUEST 2 LED HB L protective grid RAL7016 single suspension
699955	QUEST 2 LED HB M protective grid RAL7016 single suspension
699962	QUEST 2 LED L protective grid RAL7016
699979	QUEST 2 LED M protective grid RAL7016




QUEST 2 LED M - recessed frame (699993)



QUEST 2 LED L - recessed frame (699986)



QUEST 2 LED L protective grid RAL7016 (699962)



QUEST 2 LED M protective grid RAL7016 (699979)