

INDUSTRY 2 LED 1210MM 7000LM IP23 LS2 840 90° (45W)

DETAILED CARD



TECHNICAL PARAMETERS

| | |
|---|------|
| Rated power of the luminaire [W]*: | 45 |
| Ingress protection: | IP23 |
| Impact resistance: | IK07 |
| Luminous flux [lm]*: | 7000 |
| Colour temperature [K]: | 4000 |
| Energy efficiency class: | C |
| Optics: | lens |
| Beam angle [°]: | 90 |

CHARACTERISTICS

Galvanized steel sheet Industrial luminaire with IP23, with in-built energy-saving LED modules. Thanks to line lenses, following light distribution angles are available: 90°, 60°, 45°.

APPLICATION

Luminaire intended for warehouses, large stores, production halls and sports facilities. Meant for new installations and replacement of traditional T8 & T5 luminaires with energy saving LED sources.


INDUSTRY 2 LED 1210MM 7000LM IP23 LS2 840 90° (45W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

| | | | |
|-----------------------------------|---------------|----------------------------------|------------------------------|
| Index: | 672019 | Material of the body: | galvanized steel sheet |
| EAN: | 5905963672019 | Colour of the body: | silver |
| Rated power of the luminaire [W]: | 45 | Dimensions (H/W/T/S) [mm]: | 1210/137/70 |
| Luminous flux [lm]: | 7000 | Impact resistance: | IK07 |
| Supply voltage [V]: | 220 - 240 | Ingress protection: | IP23 |
| Frequency [Hz]: | 50 - 60 | Mounting version: | surface, suspended |
| Luminous efficacy [lm/W]: | 156 | Working temperature [°C]: | from -20 to +35 |
| Energy efficiency class: | C | Wire type: | 5x2,5 |
| Electrical protection class: | I | Through wiring: | LS2 |
| Colour temperature [K]: | 4000 | Net weight [kg]: | 3.200 |
| Colour rendering index: | >80 | Warranty [years]: | 5 |
| SDCM: | ≤ 3 | The number of implement units: | 1 |
| Power factor: | 0.92 | Warranty [years]: | 5 |
| LED lifespan L70B50 [h]: | 100000 | CE certificate: | 165/2023 |
| LED lifespan L80B20 [h]: | 62000 | Manual: | Download PDF |
| LED lifespan L90B10 [h]: | 31000 | Lumen maintenance after 50000h: | 83 |
| Beam angle [°]: | 90 | Lumen maintenance after 75000h: | 76 |
| Optics: | lens | Lumen maintenance after 100000h: | 69 |
| Optics material: | PMMA | | |

LIGHT CURVES



INDUSTRY 2 LED 1210MM 7000LM IP23 LS2 840 90° (45W)

DETAILED CARD

ACCESSORIES AVAILABLE

| index | Name |
|--------|---|
| 541247 | INDUSTRY LED suspension cord for chain (pack of 2) |
| 543944 | INDUSTRY LED pendant hook on wire (pack of 2) |
| 541254 | INDUSTRY LED protective grid 1490mm (60/72/90/102W) |
| 908200 | TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) |
| 540011 | INDUSTRY LED raster 1210mm |
| 540004 | INDUSTRY LED raster 1490mm (60/72/90/102W) |
| 541599 | INDUSTRY LED protective grid 1210mm |
| 539992 | INDUSTRY LED protective grid 1490mm x3 (for 153W version) |



INDUSTRY LED suspension cord for chain (pack of 2) (541247)



INDUSTRY LED pendant hook on wire (pack of 2) (543944)



INDUSTRY LED protective grid 1490mm (60/72/90/102W) (541254)



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



INDUSTRY LED raster 1210mm (540011)



INDUSTRY LED raster 1490mm (60/72/90/102W) (540004)



INDUSTRY LED protective grid 1210mm (541599)



INDUSTRY LED protective grid 1490mm x3 (for 153W version) (539992)

Card creation date: 13 March 2024

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 165/2023