

# INDUSTRY 2 LED 1490MM 13550LM IP23 DALI LS2 840 60° (91W)

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Rated power of the luminaire [W]*:</b>	91
<b>Ingress protection:</b>	IP23
<b>Impact resistance:</b>	IK07
<b>Luminous flux [lm]*:</b>	13550
<b>Colour temperature [K]:</b>	4000
<b>Energy efficiency class:</b>	C
<b>Optics:</b>	lens
<b>Beam angle [°]:</b>	60

## CHARACTERISTICS

Galvanized steel sheet Industrial luminaire with IP23, with in-built energy-saving LED modules. Thanks to line lenses, following light distribution angles are available: 90°, 60°, 45°.

## APPLICATION

Luminaire intended for warehouses, large stores, production halls and sports facilities. Meant for new installations and replacement of traditional T8 & T5 luminaires with energy saving LED sources.

# INDUSTRY 2 LED 1490MM 13550LM IP23 DALI LS2 840 60° (91W)

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	672514	Material of the body:	galvanized steel sheet
EAN:	5905963672514	Colour of the body:	silver
Rated power of the luminaire [W]:	91	Dimensions (H/W/T/S) [mm]:	1490/137/70
Colour temperature [K]:	4000	Impact resistance:	IK07
Luminous flux [lm]:	13550	Ingress protection:	IP23
Supply voltage [V]:	220 - 240	Mounting version:	surface, suspended
Frequency [Hz]:	50 - 60	Working temperature [°C]:	from -20 to +35
Luminous efficacy [lm/W]:	149	DIMM DALI:	yes
Energy efficiency class:	C	Through wiring:	LS2
Electrical protection class:	I	Control:	DALI
Colour rendering index:	>80	Wire type:	7x2,5
SDCM:	≤ 3	Net weight [kg]:	3.900
Power factor:	0.92	Warranty [years]:	5
LED lifespan L70B50 [h]:	100000	Additional accessories:	protective grid, anti-glare louvre, hook for mounting on a rope
LED lifespan L80B20 [h]:	62000	The number of implement units:	1
Beam angle [°]:	60	Warranty [years]:	5
LED lifespan L90B10 [h]:	31000	CE certificate:	<a href="#">165/2023</a>
Optics:	lens	Manual:	<a href="#">Download PDF</a>
Optics material:	PMMA	Plik LDT:	

# INDUSTRY 2 LED 1490MM 13550LM IP23 DALI LS2 840 60° (91W)

DETAILED CARD

## ACCESSORIES AVAILABLE

index	Name
541247	INDUSTRY LED suspension cord for chain (pack of 2)
543944	INDUSTRY LED pendant hook on wire (pack of 2)
541254	INDUSTRY LED protective grid 1490mm (60/72/90/102W)
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
540011	INDUSTRY LED raster 1210mm
540004	INDUSTRY LED raster 1490mm (60/72/90/102W)
541599	INDUSTRY LED protective grid 1210mm
539992	INDUSTRY LED protective grid 1490mm x3 (for 153W version)



INDUSTRY LED suspension cord for chain (pack of 2) (541247)




INDUSTRY LED pendant hook on wire (pack of 2) (543944)




INDUSTRY LED protective grid 1490mm (60/72/90/102W) (541254)



TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)



INDUSTRY LED raster 1210mm (540011)



INDUSTRY LED raster 1490mm (60/72/90/102W) (540004)



INDUSTRY LED protective grid 1210mm (541599)



INDUSTRY LED protective grid 1490mm x3 (for 153W version) (539992)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 165/2023