INDUSTRY 2 LED 1490MM 20200LM IP23 DALI LS1 840 90° (134W)

DETAILED CARD





TECHNICAL PARAMETERS

Rated power of the luminaire [W]*:	134
Ingress protection:	IP23
Impact resistance:	IK07
Luminous flux [lm]*:	20200
Colour temperature [K]:	4000
Energy efficiency class:	С
Optics:	lens
Beam angle [°]:	90

CHARACTERISTICS

Galvanized steel sheet Industrial luminaire with IP23, with in-built energy-saving LED modules. Thanks to line lenses, following light distribution angles are available: 90°, 60°, 45°.

APPLICATION

Luminaire intended for warehouses, large stores, production halls and sports facilities. Meant for new installations and replacement of traditional T8 & T5 luminaires with energy saving LED sources.



INDUSTRY 2 LED 1490MM 20200LM IP23 DALI LS1 840 90° (134W)

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	672187
EAN:	5905963672187
Rated power of the luminaire [W]:	134
Luminous flux [Im]:	20200
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	150
Energy efficiency class:	С
Electrical protection class:	1
Colour temperature [K]:	4000
Color rendering index (Ra) >: 80	
SDCM:	3
Power factor:	0.92
LED lifespan L70B50 [h]:	100000
LED lifespan L80B20 [h]:	62000
LED lifespan L90B10 [h]:	31000
Beam angle [°]:	90
Optics:	lens

Optics material:	PMMA	
Material of the body:	galvanized steel sheet	
Colour of the body:	silver	
Dimensions (H/W/T/S) [mm]:	1490/190/70	
Impact resistance:	IK07	
Ingress protection:	IP23	
Mounting version:	surface, suspended	
Working temperature [°C]:	from -20 to +35	
DIMM DALI:	yes	
Control:	DALI	
Through wiring:	LS1	
Net weight [kg]:	4.750	
Warranty [years]:	5	
The number of implement units:	1	
Warranty [years]:	5	
CE certificate:	165/2023	
Manual:	Download PDF	
Plik LDT:	<u>Download</u>	




INDUSTRY 2 LED 1490MM 20200LM IP23 DALI LS1 840 90° (134W)

DETAILED CARD

ACCESSORIES AVAILABLE


index	Name
541247	INDUSTRY LED suspension cord for chain (pack of 2)
543944	INDUSTRY LED pendant hook on wire (pack of 2)
541254	INDUSTRY LED protective grid 1490mm (60/72/90/102W)
908200	TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2)
540011	INDUSTRY LED raster 1210mm
540004	INDUSTRY LED raster 1490mm (60/72/90/102W)
541599	INDUSTRY LED protective grid 1210mm
539992	INDUSTRY LED protective grid 1490mm x3 (for 153W version)



INDUSTRY LED suspension cord for chain (pack of 2) (541247)




INDUSTRY LED pendant hook on wire (pack of 2) (543944)




INDUSTRY LED protective grid 1490mm (60/72/90/102W) (541254)




TYTAN LED. ATLAS LED. INDUSTRY LED - adjustable handle (set of 2) (908200)




INDUSTRY LED raster 1210mm (540011)



INDUSTRY LED raster 1490mm (60/72/90/102W) (540004)



INDUSTRY LED protective grid 1210mm (541599)



INDUSTRY LED protective grid 1490mm x3 (for 153W version) (539992)

Card creation date: 08 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

