

# SOLANTO N 600MM 3570LM 840 IP20 I CL. DALI OPAL WHITE 38W

DETAILED CARD



## TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	38
Colour temperature [K]:	4000
Luminous flux of the luminaire [lm] - range:	3570
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PS
Diffuser type:	OPAL
Colour of the body:	white

## CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

## APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

# SOLANTO N 600MM 3570LM 840 IP20 I CL. DALI OPAL WHITE 38W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

Index:	463020	LED lifespan L90B10 [h]:	34000
EAN:	5905963463020	Diffuser material:	PS
Light source:	LED module	Diffuser type:	OPAL
Rated power [W] - range:	38	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	3570	Colour of the body:	white
Supply voltage [V]:	220 - 240	Ring colour:	white
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	ø602/68
Luminous efficacy [lm/W]:	94	Ingress protection:	IP20
Energy efficiency class:	D	Mounting version:	surface
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	4000	Net weight [kg]:	3.850
Colour rendering index:	80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	<a href="#">217/2023</a>
LED lifespan L70B50 [h]:	112000	Manual:	<a href="#">Download PDF</a>
LED lifespan L80B20 [h]:	70 000	Plik LDT:	<a href="#">Download</a>

Card creation date: 08 May 2025  
The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 217/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: [hello@lenalighting.pl](mailto:hello@lenalighting.pl), [www.lenalighting.pl](http://www.lenalighting.pl)