SOLANTO N 600MM 3600LM 840 IP20 I CL. DALI OPAL BLACK 53W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	53
Colour temperature [K]:	4000
Luminous flux of the luminaire [lm] - range:	3600
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PS
Diffuser type:	OPAL
Colour of the body:	black

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

SOLANTO N 600MM 3600LM 840 IP20 I CL. DALI OPAL BLACK 53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463167	**Working temperature [°C]:**	from 0 to +35
EAN:	5905963463167	**Diffuser material:**	PS
Light source:	LED module	**Diffuser type:**	OPAL
Rated power [W] - range:	53	**Material of the body:**	Steel
Luminous flux of the luminaire [lm] - range:	3600	**Colour of the body:**	black
Supply voltage [V]:	220 - 240	**Ring colour:**	black
Frequency [Hz]:	50 - 60	**Dimensions (H/W/T/S) [mm]:**	ø602/68
Luminous efficacy [lm/W]:	68	**Ingress protection:**	IP20
Energy efficiency class:	F	**Mounting version:**	surface
Electrical protection class:	I	**DIMM DALI:**	yes
Colour temperature [K]:	4000	**Net weight [kg]:**	3.850
Color rendering index (Ra) >:	80	**Warranty [years]:**	5
SDCM:	3	**CE certificate:**	217/2023
LED lifespan L70B50 [h]:	112000	**Manual:**	Download PDF
LED lifespan L80B10 [h]:	70 000	**ISO Certificates:**	9001:2015, 14001:2015, 45001:2018, 50001:2018
LED lifespan L90B10 [h]:	34000	**Plik LDT:**	Download

Card creation date: 24 July 2026

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

This product is a subject to electric andelectronic waste equipment regulations (WEEE).

Certificate CE - Nr: 217/2023

Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl