

SOLANTO N 600MM 4500LM 830 IP20 I CL. DALI OPAL WHITE 53W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	53
Colour temperature [K]:	3000
Luminous flux of the luminaire [lm] - range:	4500
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PS
Diffuser type:	OPAL
Colour of the body:	white

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

SOLANTO N 600MM 4500LM 830 IP20 I CL. DALI OPAL WHITE 53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463051	LED lifespan L90B10 [h]:	34000
EAN:	5905963463051	Diffuser material:	PS
Light source:	LED module	Diffuser type:	OPAL
Rated power [W] - range:	53	Material of the body:	Steel
Luminous flux of the luminaire [lm] - range:	4500	Colour of the body:	white
Supply voltage [V]:	220 - 240	Ring colour:	white
Frequency [Hz]:	50 - 60	Dimensions (H/W/T/S) [mm]:	ø602/68
Luminous efficacy [lm/W]:	85	Ingress protection:	IP20
Energy efficiency class:	E	Mounting version:	surface
Electrical protection class:	I	DIMM DALI:	yes
Colour temperature [K]:	3000	Net weight [kg]:	3.850
Colour rendering index:	80	Warranty [years]:	5
SDCM:	≤ 3	CE certificate:	217/2023
LED lifespan L70B50 [h]:	112000	Manual:	Download PDF
LED lifespan L80B20 [h]:	70 000	Plik LDT:	Download