SOLANTO N 900MM 4500LM 830 IP20 I CL. DALI OPAL WHITE 53W

DETAILED CARD



CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

TECHNICAL PARAMETERS

Light source: LED module Rated power [W] - range: 53 3000 Colour temperature [K]: Luminous flux of the luminaire [Im] -4500 range: IP20 Ingress protection: **Electrical protection class:** Diffuser material: PS **OPAL** Diffuser type: Colour of the body: white



SOLANTO N 900MM 4500LM 830 IP20 I CL. DALI OPAL WHITE 53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

463297
5905963463297
LED module
53
4500
220 - 240
50 - 60
85
Е
1
3000
80
3
112000

LED lifespan L90B10 [h]:	34000
Diffuser material:	PS
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	white
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	ø900/68
Ingress protection:	IP20
Mounting version:	surface
DIMM DALI:	yes
Net weight [kg]:	6.160
Warranty [years]:	5
CE certificate:	<u>217/2023</u>
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



