SOLANTO Z 600MM 3600LM 840 IP20 I CL. DALI OPAL BLACK 53W

DETAILED CARD





TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	53
Colour temperature [K]:	4000
Luminous flux of the luminaire [lm] - range:	3600
Ingress protection:	IP20
Electrical protection class:	1
Diffuser material:	PS
Diffuser type:	OPAL
Colour of the body:	black

CHARACTERISTICS

Suspended-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.



SOLANTO Z 600MM 3600LM 840 IP20 I CL. DALI OPAL BLACK 53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463228
EAN:	5905963463228
Light source:	LED module
Rated power [W] - range:	53
Luminous flux of the luminaire [lm] - range:	3600
Supply voltage [V]:	220 - 240
Frequency [Hz]:	50 - 60
Luminous efficacy [lm/W]:	68
Energy efficiency class:	F
Electrical protection class:	I
Colour temperature [K]:	4000
Color rendering index (Ra) >:	80
SDCM:	3
LED lifespan L70B50 [h]:	112000
LED lifespan L80B20 [h]:	70 000
LED lifespan L90B10 [h]:	34000

Diffuser material:	PS
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	black
Ring colour:	black
Dimensions (H/W/T/S) [mm]:	ø602/32
Ingress protection:	IP20
Mounting version:	suspended
DIMM DALI:	yes
Cable length [m]:	1.20
Net weight [kg]:	2.550
Warranty [years]:	5
CE certificate:	218/2023
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



