
## SOLANTO Z 600MM 4500LM 830 IP20 I CL. DALI OPAL WHITE 53W

**DETAILED CARD** 





### **TECHNICAL PARAMETERS**

| Light source:                                | LED module |
|--|------------|
| Rated power [W] - range:                     | 53         |
| Colour temperature [K]:                      | 3000       |
| Luminous flux of the luminaire [lm] - range: | 4500       |
| Ingress protection:                          | IP20       |
| Electrical protection class:                 | I          |
| Diffuser material:                           | PS         |
| Diffuser type:                               | OPAL       |
| Colour of the body:                          | white      |
|  |            |

#### **CHARACTERISTICS**

Suspended-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

#### **APPLICATION**

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.



# SOLANTO Z 600MM 4500LM 830 IP20 I CL. DALI OPAL WHITE 53W

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

| Index:                                       | 463112        |
|--|---------------|
| index:                                       | 1.21.2        |
| EAN:   | 5905963463112 |
| Light source:                                | LED module    |
| Rated power [W] - range:                     | 53            |
| Luminous flux of the luminaire [lm] - range: | 4500          |
| Supply voltage [V]:                          | 220 - 240     |
| Frequency [Hz]:                              | 50 - 60       |
| Luminous efficacy [lm/W]:                    | 85            |
| Energy efficiency class:                     | E             |
| Electrical protection class:                 | I             |
| Colour temperature [K]:                      | 3000          |
| Color rendering index (Ra) >:                | 80            |
| SDCM:  | 3             |
| LED lifespan L70B50 [h]:                     | 112000        |
| LED lifespan L80B20 [h]:                     | 70 000        |
| LED lifespan L90B10 [h]:                     | 34000         |

| Diffuser material:         | PS              |
|----------------------------|-----------------|
| Diffuser type:             | OPAL            |
| Material of the body:      | Steel           |
| Colour of the body:        | white           |
| Ring colour:               | white           |
| Dimensions (H/W/T/S) [mm]: | ø602/32         |
| Ingress protection:        | IP20            |
| Mounting version:          | suspended       |
| DIMM DALI:                 | yes             |
| Cable length [m]:          | 1.20            |
| Net weight [kg]:           | 2.550           |
| Warranty [years]:          | 5               |
| CE certificate:            | <u>218/2023</u> |
| Manual:                    | Download PDF    |
| Plik LDT:                  | Download        |

Card creation date: 14 November 2025



