

SOLANTO Z 900MM 2590LM 840 IP20 I CL. DALI OPAL BLACK 38W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	38
Colour temperature [K]:	4000
Luminous flux of the luminaire [lm] - range:	2590
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PS
Diffuser type:	OPAL
Colour of the body:	black

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

SOLANTO Z 900MM 2590LM 840 IP20 I CL. DALI OPAL BLACK 38W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463440	Diffuser material:	PS
EAN:	5905963463440	Diffuser type:	OPAL
Light source:	LED module	Material of the body:	Steel
Rated power [W] - range:	38	Colour of the body:	black
Luminous flux of the luminaire [lm] - range:	2590	Ring colour:	black
Supply voltage [V]:	220 - 240	Dimensions (H/W/T/S) [mm]:	ø900/32
Frequency [Hz]:	50 - 60	Ingress protection:	IP20
Luminous efficacy [lm/W]:	68	Mounting version:	suspended
Energy efficiency class:	F	DIMM DALI:	yes
Electrical protection class:	I	Cable length [m]:	1
Colour temperature [K]:	4000	Net weight [kg]:	4.080
Color rendering index (Ra) >:	80	Warranty [years]:	5
SDCM:	3	CE certificate:	218/2023
LED lifespan L70B50 [h]:	112000	Manual:	Download PDF
LED lifespan L80B10 [h]:	70 000	Plik LDT:	Download
LED lifespan L90B10 [h]:	34000		

Card creation date: 14 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 218/2023