


SOLANTO Z 900MM 4980LM 840 IP20 I CL. DALI OPAL WHITE 53W

DETAILED CARD



TECHNICAL PARAMETERS

Light source:	LED module
Rated power [W] - range:	53
Colour temperature [K]:	4000
Luminous flux of the luminaire [lm] - range:	4980
Ingress protection:	IP20
Electrical protection class:	I
Diffuser material:	PS
Diffuser type:	OPAL
Colour of the body:	white

CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

SOLANTO Z 900MM 4980LM 840 IP20 I CL. DALI OPAL WHITE 53W

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	463341	SDCM:	≤ 3
EAN:	5905963463341	LED lifespan L70B50 [h]:	112000
Light source:	LED module	LED lifespan L80B20 [h]:	70 000
Rated power [W] - range:	53	LED lifespan L90B10 [h]:	34000
Luminous flux of the luminaire [lm] - range:	4980	Diffuser material:	PS
Colour temperature [K]:	4000	Diffuser type:	OPAL
Colour of the body:	white	Material of the body:	Steel
DIMM DALI:	yes	Ring colour:	white
Dimensions (H/W/T/S) [mm]:	ø900/32	Ingress protection:	IP20
Supply voltage [V]:	220 - 240	Cable length [m]:	1.20
Mounting version:	suspended	Net weight [kg]:	4.080
Frequency [Hz]:	50 - 60	Warranty [years]:	5
Luminous efficacy [lm/W]:	94	CE certificate:	218/2023
Energy efficiency class:	D	Manual:	Download PDF
Electrical protection class:	I	Plik LDT:	
Colour rendering index:	>80		

Card creation date: 02 January 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 218/2023