

# SOLANTO MULTI N 900MM 1890-3330LM 830 IP20 I CL. OPAL BLACK 30-53W

DETAILED CARD



## TECHNICAL PARAMETERS

|   |                     |
|---|---------------------|
| <b>Light source:</b>                                | LED module          |
| <b>Rated power [W] - range:</b>                     | 30/38/45/53         |
| <b>Colour temperature [K]:</b>                      | 3000                |
| <b>Luminous flux of the luminaire [lm] - range:</b> | 1890/2400/2800/3330 |
| <b>Ingress protection:</b>                          | IP20                |
| <b>Electrical protection class:</b>                 | I                   |
| <b>Diffuser material:</b>                           | PS                  |
| <b>Diffuser type:</b>                               | OPAL                |
| <b>Colour of the body:</b>                          | black               |

## CHARACTERISTICS

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

## APPLICATION

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.

# SOLANTO MULTI N 900MM 1890-3330LM 830 IP20 I CL. OPAL BLACK 30-53W

DETAILED CARD

## TECHNICAL PARAMETERS TABLE

|  |                     |                            |                              |
|--|---------------------|----------------------------|------------------------------|
| Index:                                       | 463372              | LED lifespan L90B10 [h]:   | 34000                        |
| EAN:   | 5905963463372       | Diffuser material:         | PS                           |
| Light source:                                | LED module          | Diffuser type:             | OPAL                         |
| Rated power [W] - range:                     | 30/38/45/53         | Material of the body:      | Steel                        |
| Luminous flux of the luminaire [lm] - range: | 1890/2400/2800/3330 | Colour of the body:        | black                        |
| Supply voltage [V]:                          | 220 - 240           | Ring colour:               | black                        |
| Frequency [Hz]:                              | 50 - 60             | Dimensions (H/W/T/S) [mm]: | ø900/68                      |
| Luminous efficacy [lm/W]:                    | 63                  | Ingress protection:        | IP20                         |
| Energy efficiency class:                     | F                   | Mounting version:          | surface                      |
| Electrical protection class:                 | I                   | Net weight [kg]:           | 5,840                        |
| Colour temperature [K]:                      | 3000                | Warranty [years]:          | 5                            |
| Color rendering index (Ra) >:                | 80                  | CE certificate:            | <a href="#">217/2023</a>     |
| SDCM:  | 3                   | Manual:                    | <a href="#">Download PDF</a> |
| LED lifespan L70B50 [h]:                     | 112000              | Plik LDT:                  | <a href="#">Download</a>     |
| LED lifespan L80B10 [h]:                     | 70 000              |                            |                              |

Card creation date:14 November 2025

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 217/2023



Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl