## SOLANTO MULTI N 900MM 2820-4980LM 840 IP20 I CL. OPAL WHITE 30-53W

**DETAILED CARD** 



### **TECHNICAL PARAMETERS**

**Light source:** LED module

**Rated power [W] - range:** 30/38/45/53

Colour temperature [K]: 4000

Luminous flux of the luminaire [lm] -

range:

2820/3570/4200/4980

Ingress protection: IP20

Electrical protection class:

Diffuser material: PS

Diffuser type: OPAL

Colour of the body: white

#### **CHARACTERISTICS**

Suspended or surface-mounted ring-shaped LED luminaire, allowing for an attractive arrangement of representative interiors. The luminaire is made of steel powder coated in white, black or other color to fit the character of the interior. The milky diffuser made with thermoforming method emphasises the decorative character of the luminaire. The pendant option includes a complete pendant system with a central box.

Multi LED versions allow you to choose from 4 flux and power settings increasing the versatility and functionality of the luminaire, while reducing the number of indexes to the necessary minimum.

#### **APPLICATION**

SOLANTO is an extremely glamorous pendant or surface mounted luminaire, dedicated to such interiors as lobbies, receptions, shopping malls, showrooms. It can be also used in apartments and apartments, perfectly fitting into stylish surroundings.



# **SOLANTO MULTI N 900MM 2820-4980LM 840 IP20 I CL. OPAL WHITE 30-53W**

**DETAILED CARD** 

#### **TECHNICAL PARAMETERS TABLE**

463242
5905963463242
LED module
30/38/45/53
2820/3570/4200/4980
220 - 240
50 - 60
94
D
1
4000
80
3
112000
70 000

LED lifespan L90B10 [h]:	34000
LED mespan E90Bio [n].	34000
Diffuser material:	PS
Diffuser type:	OPAL
Material of the body:	Steel
Colour of the body:	white
Ring colour:	white
Dimensions (H/W/T/S) [mm]:	ø900/68
Ingress protection:	IP20
Mounting version:	surface
Net weight [kg]:	5.840
Warranty [years]:	5
CE certificate:	<u>217/2023</u>
Manual:	Download PDF
Plik LDT:	Download

Card creation date: 14 November 2025



